



SIMATIC ET 200SP, BaseUnit BU15-P16+A10+2D, BU type A0, Pack quantity: 10 units, Push-in terminals, with 10 AUX terminals, New load group, WxH: 15 mmx141 mm

Figure similar

General information	
Product type designation	BU type A0
HW functional status	From FS07
Supply voltage	
Rated value (DC)	24 V
external protection for power supply lines	Yes; 24 V DC/10 A miniature circuit breaker with type B or C tripping characteristic
Current carrying capacity	
For P1 and P2 bus, max.	10 A
For AUX bus, max.	10 A
For process terminals, max.	2 A
Hardware configuration	
Formation of potential groups	
<ul style="list-style-type: none"> <li>New potential group</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Potential group continued from the left</li> </ul>	No
Slots	
<ul style="list-style-type: none"> <li>Number of slots</li> </ul>	1; Type A0
Potential separation	
between the potential groups	Yes
Isolation	
Isolation tested with	707 V DC (type test)
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> <li>horizontal installation, min.</li> </ul>	-30 °C
<ul style="list-style-type: none"> <li>horizontal installation, max.</li> </ul>	60 °C
<ul style="list-style-type: none"> <li>vertical installation, min.</li> </ul>	-30 °C
<ul style="list-style-type: none"> <li>vertical installation, max.</li> </ul>	50 °C
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> <li>Installation altitude above sea level, max.</li> </ul>	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
Accessories	
Color coding labels	
<ul style="list-style-type: none"> <li>for process terminals</li> </ul>	CC00 to CC09
<ul style="list-style-type: none"> <li>for AUX terminals</li> </ul>	CC71 to CC73
<ul style="list-style-type: none"> <li>for add-on terminals</li> </ul>	does not exist
connection method	
Terminals	
<ul style="list-style-type: none"> <li>Terminal type</li> </ul>	Push-in terminal
<ul style="list-style-type: none"> <li>system-integrated shield connection</li> </ul>	Yes; Optional
<ul style="list-style-type: none"> <li>Conductor cross-section, min.</li> </ul>	0.14 mm <sup>2</sup> ; AWG 26

- Conductor cross-section, max. 2.5 mm<sup>2</sup>; AWG 14
- Number of process terminals to I/O module 16
- Number of terminals to AUX bus 10
- Number of add-on terminals 0
- Number of terminals with connection to P1 and P2 bus 2

#### Dimensions

Width	15 mm
Height	141 mm
Depth	35 mm

#### Weights

Weight, approx.	50 g
-----------------	------

#### Classifications

	Version	Classification
eClass	14	27-24-26-03
eClass	12	27-24-26-03
eClass	9.1	27-24-26-03
eClass	9	27-24-26-03
eClass	8	27-24-26-03
eClass	7.1	27-24-26-03
eClass	6	27-24-26-03
ETIM	9	EC001598
ETIM	8	EC001598
ETIM	7	EC001598
IDEA	4	3560
UNSPSC	15	32-15-17-04

#### Approvals / Certificates

General Product Approval	Marine / Shipping
--------------------------	-------------------



[Manufacturer Declaration](#)



last modified:

3/12/2024