

IEC cable, China, 230 V AC, angled, for IPC and power supply units, scope of supply: 1 IEC cable



General information	
Product type designation	Cable for non-heating apparatus
Interfaces	
Interfaces/bus type	Line-side, country-specific connector: Type I: GB 1002 (China), AS 3112 (Australia), IRAM 2073 (Argentina)
Device-side interface	
• Number of pins device-side	3; Female, C13 connector type
Standards, approvals, certificates	
CE mark	Yes
CSA approval	Yes; N11419
KC approval	No
EAC (formerly Gost-R)	No
CCC	Yes
RoHS conformity	Yes
Ambient conditions	
Suited for indoor use	Yes; Max. 10 A
Ambient temperature during operation	
• min.	-10 °C
• max.	50 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	85 °C
Relative humidity	
• Operation, max.	90 %
Cables	
Cable length	3 m
Color of cable sheath	Black
Weights	
Weight, approx.	280 g
Scope of supply	
Delivery quantity in pieces	1; AC cable for CN
Other	
Merchandise	Yes; PRC/3-H05VVF3G100-C13W/3,00M SW9005
Manufacturer name	FELLER GmbH
Manufacturer's address	Wärndorferstraße 3, 2525 Günselsdorf, Austria; email: sales@feller-at.com
Target devices	Suitable for all appropriate DC interfaces
Note:	http://www.feller-at.com
Usable in the following products	
• Product 1	6AV6671-5CN00-0AX3
Classifications	

	Version	Classification
eClass	14	27-06-04-02
eClass	12	27-06-04-02
eClass	9.1	27-06-04-02
eClass	9	27-06-04-02
eClass	8	27-06-04-02
eClass	7.1	27-06-04-02
eClass	6	27-06-04-02
ETIM	9	EC001576
ETIM	8	EC001576
ETIM	7	EC001576
IDEA	4	4660
UNSPSC	15	39-12-14-40

Approvals / Certificates

General Product Approval



last modified:

4/19/2023