

Siemens  
EcoTech



SIMATIC S7-1500, digital input module DI 16x24 V DC AUX; 16 channels in groups of 8; for 24 V encoder; sensor supply 24 V DC; input type 2 (IEC 61131); input delay parameterizable 0.05..20 ms; isochronous mode up to 250 µs; integrated counting function up to 20 kHz; pulse stretching; chatter monitoring; signal inversion diagnostics; hardware interrupts: front connector (screw terminals or push-in) and, if applicable, order shield set separately

General information	
Product type designation	DI 16x24 V DC HS
HW functional status	From FS01
Firmware version	V1.0.0
<ul style="list-style-type: none"> <li>FW update possible</li> </ul>	Yes
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> <li>Isochronous mode</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Prioritized startup</li> </ul>	Yes
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul>	STEP 7 V17 or higher
<ul style="list-style-type: none"> <li>STEP 7 configurable/integrated from version</li> </ul>	V5.5 SP3 / -
<ul style="list-style-type: none"> <li>PROFIBUS from GSD version/GSD revision</li> </ul>	V1.0 / V5.1
<ul style="list-style-type: none"> <li>PROFINET from GSD version/GSD revision</li> </ul>	V2.3 / -
Operating mode	
<ul style="list-style-type: none"> <li>DI</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Counter</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Oversampling</li> </ul>	Yes
<ul style="list-style-type: none"> <li>MSI</li> </ul>	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption, max.	550 mA
Encoder supply	
Number of outputs	16; 2x 24 V DC
Short-circuit protection	Yes
24 V encoder supply	
<ul style="list-style-type: none"> <li>24 V</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Short-circuit protection</li> </ul>	Yes; Per group, electronic
<ul style="list-style-type: none"> <li>Output current, max.</li> </ul>	150 mA; per group
<ul style="list-style-type: none"> <li>Output current per module, max.</li> </ul>	300 mA
Power	
Power consumption from the backplane bus	0.6 W
Power loss	

Power loss, typ.	7 W
<b>Digital inputs</b>	
Number of digital inputs	16
Digital inputs, parameterizable	Yes
Source/sink input	P-reading
Input characteristic curve in accordance with IEC 61131, type 2	Yes
Pulse extension	Yes; 0.05 s, 0.1 s, 0.2 s, 0.5 s, 1 s, 2 s
Edge evaluation	Yes; Positive edge, negative edge
Signal change flutter	Yes; 2 to 32 signal changes
Flutter observation window	Yes; 0.5 s, 1 s to 100 s in 1-s steps
<b>Digital input functions, parameterizable</b>	
<ul style="list-style-type: none"> <li>• Gate start/stop</li> <li>• Freely usable digital input</li> <li>• Counter <ul style="list-style-type: none"> <li>— Number, max.</li> <li>— Counting frequency, max.</li> <li>— Counting width</li> <li>— Counting direction up/down</li> </ul> </li> <li>• Digital input with oversampling <ul style="list-style-type: none"> <li>— Number, max.</li> <li>— Values per cycle, max.</li> <li>— Resolution, min.</li> </ul> </li> </ul>	<ul style="list-style-type: none"> <li>Yes; software/hardware gate</li> <li>Yes</li> <li>4; 4 totalizers max. 10 kHz or 2 totalizers max. 20 kHz + 2 totalizers max. 10 kHz</li> <li>20 kHz</li> <li>32 bit</li> <li>Yes</li> <li>Yes</li> <li>16</li> <li>16</li> <li>15.625 µs</li> </ul>
<b>Input voltage</b>	
<ul style="list-style-type: none"> <li>• Rated value (DC)</li> <li>• for signal "0"</li> <li>• for signal "1"</li> </ul>	<ul style="list-style-type: none"> <li>24 V</li> <li>-30 to +5 V</li> <li>+11 to +30V</li> </ul>
<b>Input current</b>	
<ul style="list-style-type: none"> <li>• for signal "1", typ.</li> </ul>	9 mA
<b>Input delay (for rated value of input voltage)</b>	
for standard inputs	
<ul style="list-style-type: none"> <li>— parameterizable</li> <li>— at "0" to "1", min.</li> <li>— at "0" to "1", max.</li> <li>— at "1" to "0", min.</li> <li>— at "1" to "0", max.</li> </ul>	<ul style="list-style-type: none"> <li>Yes; 0.05 / 0.1 / 0.4 / 0.8 / 1.6 / 3.2 / 12.8 / 20 ms</li> <li>0.05 ms</li> <li>20 ms</li> <li>0.05 ms</li> <li>20 ms</li> </ul>
for interrupt inputs	
<ul style="list-style-type: none"> <li>— parameterizable</li> </ul>	Yes
for technological functions	
<ul style="list-style-type: none"> <li>— parameterizable</li> </ul>	Yes
<b>Cable length</b>	
<ul style="list-style-type: none"> <li>• shielded, max.</li> <li>• unshielded, max.</li> </ul>	<ul style="list-style-type: none"> <li>1 000 m; 600 m for technological functions; depending on input frequency, encoder and cable quality; max. 50 m at 20 kHz</li> <li>600 m; for technological functions: No</li> </ul>
<b>Encoder</b>	
Connectable encoders	
<ul style="list-style-type: none"> <li>• 2-wire sensor <ul style="list-style-type: none"> <li>— permissible quiescent current (2-wire sensor), max.</li> </ul> </li> </ul>	<ul style="list-style-type: none"> <li>Yes</li> <li>2 mA</li> </ul>
<b>Isochronous mode</b>	
Filtering and processing time (TCI), min.	60 µs; At 50 µs filter time
Bus cycle time (TDP), min.	250 µs
<b>Interrupts/diagnostics/status information</b>	
Diagnostics function	Yes
<b>Alarms</b>	
<ul style="list-style-type: none"> <li>• Diagnostic alarm</li> <li>• Hardware interrupt</li> </ul>	<ul style="list-style-type: none"> <li>Yes</li> <li>Yes</li> </ul>
<b>Diagnoses</b>	
<ul style="list-style-type: none"> <li>• Monitoring the supply voltage</li> <li>• Monitoring of encoder power supply</li> <li>• Wire-break</li> <li>• Short-circuit</li> </ul>	<ul style="list-style-type: none"> <li>Yes</li> <li>Yes; short-circuit</li> <li>Yes; to I &lt; 350 µA</li> <li>No</li> </ul>

<b>Diagnostics indication LED</b>	
• RUN LED	Yes; green LED
• ERROR LED	Yes; red LED
• Monitoring of the supply voltage (PWR-LED)	Yes; green LED
• Channel status display	Yes; green LED
• for channel diagnostics	Yes; red LED
• for module diagnostics	Yes; red LED

**Potential separation**

<b>Potential separation channels</b>	
• between the channels	No
• between the channels, in groups of	8
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	Yes
• between the channels and the power supply of the electronics	No

**Isolation**

Isolation tested with	707 V DC (type test)
-----------------------	----------------------

**Standards, approvals, certificates**

Suitable for safety functions	No
-------------------------------	----

**Ecological footprint**

• environmental product declaration	Yes
-------------------------------------	-----

**Global warming potential**

— global warming potential, (total) [CO2 eq]	18.9 kg
— global warming potential, (during production) [CO2 eq]	12.1 kg
— global warming potential, (during operation) [CO2 eq]	7.66 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-1.02 kg

**product functions / security / header**

signed firmware update	No
data integrity	No

**Ambient conditions**

**Ambient temperature during operation**

• horizontal installation, min.	-30 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	-30 °C
• vertical installation, max.	40 °C

**Altitude during operation relating to sea level**

• Installation altitude above sea level, max.	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
---	--

**Dimensions**

Width	35 mm
Height	147 mm
Depth	129 mm

**Weights**

Weight, approx.	240 g
-----------------	-------

**Classifications**

	Version	Classification
eClass	14	27-24-22-04
eClass	12	27-24-22-04
eClass	9.1	27-24-22-04
eClass	9	27-24-22-04
eClass	8	27-24-22-04
eClass	7.1	27-24-22-04
eClass	6	27-24-22-04
ETIM	9	EC001419
ETIM	8	EC001419
ETIM	7	EC001419

**Approvals / Certificates**

General Product Approval	For use in hazardous locations
--------------------------	--------------------------------



[KC](#)



[FM](#)

For use in hazardous locations	Marine / Shipping
--------------------------------	-------------------

[CCC-Ex](#)



[Type Examination Certificate](#)



IECEX

[Miscellaneous](#)



ABS

Marine / Shipping
-------------------



LRS

[NK / Nippon Kaiji Kyokai](#)



RINA



RMRS

Marine / Shipping	Environment
-------------------	-------------

[CCS \(China Classification Society\)](#)



Siemens EcoTech



last modified:

10/9/2024