# **Data sheet**

## 6GK5004-1BF00-1AB2



SCALANCE XB004-1LD unmanaged Industrial Ethernet Switch for 10/100 Mbit/s; for setting up small star and line topologies; LED diagnostics, IP20, 24 V AC/DC power supply, with 4x 10/100 Mbit/s twisted pair ports with RJ45 sockets; 1 x 100 Mbit/s single-mode glass fiber-optic cable port with SC socket; manual available as a download .

product type designation		
product brand name	SCALANCE	
product type designation	XB004-1LD	
transfer rate		
transfer rate	10 Mbit/s, 100 Mbit/s	
interfaces / for communication / integrated		
number of electrical connections		
<ul> <li>for network components or terminal equipment</li> </ul>	4; RJ45	
number of 100 Mbit/s SC ports		
<ul> <li>for multimode</li> </ul>	0	
• for single mode (LD)	1	
transmission method / of the optical interface	100BaseLX LD	
interfaces / other		
number of electrical connections		
for power supply	1	
type of electrical connection		
• for power supply	3-pole terminal block	
supply voltage, current consumption, power loss		
type of voltage / 1 / of the supply voltage	DC	
<ul><li>supply voltage / 1 / rated value</li></ul>	24 V	
<ul><li>power loss [W] / 1 / rated value</li></ul>	2.4 W	
<ul> <li>supply voltage / 1 / rated value</li> </ul>	19.2 28.8 V	
<ul><li>consumed current / 1 / maximum</li></ul>	0.1 A	
<ul> <li>type of electrical connection / 1 / for power supply</li> </ul>	3-pole terminal block	
<ul> <li>product component / 1 / fusing at power supply input</li> </ul>	Yes	
fuse protection type / 1 / at input for supply voltage	0.6 A / 60 V	
type of voltage / 2 / of the supply voltage	AC	
supply voltage / 2 / rated value	19.2 28.8 V	
ambient conditions		
ambient temperature		
<ul> <li>during operation</li> </ul>	-10 +60 °C	
during storage	-40 +80 °C	
during transport	-40 +80 °C	
relative humidity		
at 25 °C / without condensation / during operation / maximum	95 %	
protection class IP	IP20	
design, dimensions and weights		
design	Box	
width	45 mm	

hoight	400 mm
height	100 mm
depth	87 mm
net weight	0.165 kg
fastening method	
• 35 mm DIN-rail mounting	Yes
wall mounting	Yes
S7-1500 rail mounting	No
product functions / management, configuration, engineering	
product function	
<ul> <li>multiport mirroring</li> </ul>	No
• CoS	Yes
switch-managed	No
PROFINET conformity class	A
product functions / redundancy	
product function	
<ul> <li>Parallel Redundancy Protocol (PRP)/operation in the PRP-network</li> </ul>	Yes
<ul> <li>Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)</li> </ul>	No
standards, specifications, approvals	
certificate of suitability	
CE marking	Yes
KC approval	Yes
Regulatory Compliance Mark (RCM)	Yes
standard	
for EMC interference emission	EN 61000-6-4 (Class A)
• for immunity to EMC	EN 61000-6-2
• for safety / from CSA and UL	UL 60950-1, CSA C22.2 No. 60950-1
standards, specifications, approvals / hazardous environments	0E 00000 1, 00/1 022.2 10. 00000 1
certificate of suitability	
• ATEX	Yes
• UKEX	Yes
• IECEX	Yes
ULhazloc approval	Yes
CCC / for hazardous zone according to GB standard	Yes
FM registration	Yes
standards, specifications, approvals / other	165
certificate of suitability	V
RoHS conformity  AND///CA  AND///CA	Yes
resistance to air pollution / conformity according to ANSI/ISA-71.04	Yes; G3
standards, specifications, approvals / Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
● total	141.3 kg
during manufacturing	15.99 kg
during operation	125.18 kg
after end of life	0.15 kg
product functions / general	
MTBF	238 a
reference code	
<ul> <li>according to IEC 81346-2</li> </ul>	KF
• according to IEC 81346-2:2019	KFE
Warranty period	5 a
product function / is supported / identification link	Yes; acc. to IEC 61406-1:2022
further information / internet links	
internet link	
internet link	
to website: Selection guide for cables and connectors	https://support.industry.siemens.com/cs/ww/en/view/109766358
	https://support.industry.siemens.com/cs/ww/en/view/109766358 https://www.siemens.com/tstcloud
• to website: Selection guide for cables and connectors	
<ul><li>to website: Selection guide for cables and connectors</li><li>to web page: selection aid TIA Selection Tool</li></ul>	https://www.siemens.com/tstcloud

• to website: Image database

• to website: CAx-Download-Manager

• to website: Industry Online Support

https://www.automation.siemens.com/bilddb

https://www.siemens.com/cax

https://support.industry.siemens.com

#### security information

security information

Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

### **Approvals / Certificates**

### **General Product Approval**



**Declaration of Con**formity









**General Product Ap**proval

**EMV** 

For use in hazardous locations



<u>KC</u>



IECEx



<u>FM</u>



KEMA

For use in hazard-

ous locations

**Test Certificates** 

**Environment** 

**Industrial Communication** 

CCC-Ex

Special Test Certificate

Confirmation



**PROFINET** 

last modified:

2/26/2025

