SIEMENS

Data sheet

6GK5722-1FC00-0AC0

product type designation



W722-1 RJ45 (ISR)

IWLAN client, SCALANCE W722-1, RJ45, 1 radio, 1 R-SMA antenna port, iFeatures support IEEE 802.11a/b/g/h/n, 2.4/5GHz, gross data rate 150 Mbit/s, 1x RJ45 max. 100 Mbit/s, 24 V DC, joint block, IP20, 0... +55 °C, WPA2/802.11i/e, observe national approvals! CERT ID: ELN-W1-RJ-E1, scope of delivery: Manuals on CD-ROM, German/English, 1x joint block; only for operation in Israel.

transfer rate			
transfer rate			
with WLAN / maximum	150 Mbit/s		
for Industrial Ethernet	10, 100 Mbit/s		
transfer rate / for Industrial Ethernet			
• minimum	10 Mbit/s		
• maximum	100 Mbit/s		
interfaces			
number of electrical connections			
 for network components or terminal equipment 	1		
for power supply	1		
 for redundant voltage supply 	0		
type of electrical connection			
 for network components or terminal equipment 	RJ45 socket		
for power supply	3-pole screw terminal		
memory			
design of the removable storage			
• C-PLUG	No		
• KEY-PLUG	No		
interfaces / wireless			
number of radio cards / permanently installed	1		
number of electrical connections / for external antenna(s)	1		
type of electrical connection / for external antenna(s)	R-SMA (socket)		
product feature / external antenna can be mounted directly on device	Yes		
supply voltage, current consumption, power loss			
type of voltage / of the supply voltage	DC		
consumed current			
at DC / at 24 V / typical	0.15 A		
power loss [W]			
at DC / at 24 V / typical	3.6 W		
supply voltage / 1			
from terminal block	19.2 V		
supply voltage / 2			
from terminal block	28.8 V		
ambient conditions			
ambient temperature			
 during operation 	0 55 °C		
 during storage 	-40 +85 °C		

during transport	-40 +85 °C
relative humidity / at 25 °C / without condensation / during	95 %
operation / maximum	
ambient condition / for operation	When used under hazardous conditions (Zone 2), the SCALANCE W761-1 RJ45 or W72x-1 RJ45 product must be installed in an enclosure. To comply with EN 50021, this enclosure must meet the requirements of at least IP 54 in compliance with EN 60529.
protection class IP	IP20
design, dimensions and weights	
width	50 mm
height	114 mm
depth	74 mm
width / of the enclosure / without antenna	50 mm
height / of the enclosure / without antenna	114 mm
depth / of the enclosure / without antenna	74 mm
net weight	0.13 kg
fastening method	
S7-300 rail mounting	No
S7-1500 rail mounting	No
35 mm DIN-rail mounting	Yes
wall mounting	No
radio frequencies	
operating frequency	
for WLAN in 2.4 GHz frequency band	2.41 2.48 GHz; depending on the country approvals
• for WLAN in 5 GHz frequency band	4.9 5.8 GHz; depending on the country approvals
product features, product functions, product components / ger	neral
product function / Access Point Mode	No
product function / client Mode	Yes
product function	
• iPCF client	Yes
• iPCF-MC client	Yes
number of iPCF-capable radio modules	1
product function / iPRP	Yes
product functions / management, configuration, engineering	
number of manageable IP addresses / in client	4
product function	
• CLI	Yes
web-based management	Yes
MIB support	Yes
TRAPs via email	Yes
 configuration with STEP 7 	Yes
configuration with STEP 7 in the TIA Portal	Yes
• WDS	No
protocol / is supported	
 Address Resolution Protocol (ARP) 	Yes
• ICMP	Yes
• Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• DCP	Yes
• LLDP	No
identification & maintenance function	
• I&M0 - device-specific information	Yes
I&M1 - higher level designation/location designation	Yes
product function / is supported / identification link	Yes; acc. to IEC 61406-1:2022
product functions / diagnostics	
product function	
 PROFINET IO diagnosis 	Yes
PROFINET IO diagnosislink check	Yes No
-	

protocol / is supported	
• SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
product functions / VLAN	
product function	
 function VLAN with IWLAN 	No
product functions / DHCP	
product function	
DHCP client	Yes
DHCP server	Yes
DHCP Option 82	Yes
product functions / redundancy	
protocol / is supported	
STP/RSTP	Yes
• MSTP	Yes
• RSTP	Yes
product functions / security	
product function	
ACL - MAC-based	Yes
 management security, ACL-IP based 	Yes
• IEEE 802.1x (radius)	Yes
NAT/NAPT	Yes
access protection according to IEEE802.11i	Yes
WPA/WPA2	Yes
• TKIP/AES	Yes
protocol / is supported	
• SSH	Yes
• RADIUS	Yes
product functions / time	
protocol / is supported	
• NTP	Yes
• SNTP	Yes
 SIMATIC time synchronization (SIMATIC Time) 	Yes
standards, specifications, approvals	
standard	
• for FM	FM 3611: Class I, Division 2, Groups A,B,C,D, T4 / Class 1, Zone 2, Group IIC, T4, FM16US0205X
for FMfor safety / from CSA and UL	
	T4, FM16US0205X
for safety / from CSA and UL	T4, FM16US0205X
for safety / from CSA and UL certificate of suitability	T4, FM16US0205X UL 60950-1 E115352, CSA C22.2 No. 60950-1
for safety / from CSA and UL certificate of suitability	T4, FM16US0205X UL 60950-1 E115352, CSA C22.2 No. 60950-1 No
for safety / from CSA and UL certificate of suitability EC Declaration of Conformity CE marking	T4, FM16US0205X UL 60950-1 E115352, CSA C22.2 No. 60950-1 No No
for safety / from CSA and UL certificate of suitability	T4, FM16US0205X UL 60950-1 E115352, CSA C22.2 No. 60950-1 No No Yes
for safety / from CSA and UL certificate of suitability EC Declaration of Conformity CE marking C-Tick E1 approval	T4, FM16US0205X UL 60950-1 E115352, CSA C22.2 No. 60950-1 No No Yes No
for safety / from CSA and UL certificate of suitability	T4, FM16US0205X UL 60950-1 E115352, CSA C22.2 No. 60950-1 No No Yes No No
for safety / from CSA and UL certificate of suitability	T4, FM16US0205X UL 60950-1 E115352, CSA C22.2 No. 60950-1 No No Yes No No No No
for safety / from CSA and UL certificate of suitability	T4, FM16US0205X UL 60950-1 E115352, CSA C22.2 No. 60950-1 No No Yes No No No No No
for safety / from CSA and UL certificate of suitability	T4, FM16US0205X UL 60950-1 E115352, CSA C22.2 No. 60950-1 No No Yes No No No No No No No
for safety / from CSA and UL certificate of suitability	T4, FM16US0205X UL 60950-1 E115352, CSA C22.2 No. 60950-1 No No Yes No No No No No No No No No
for safety / from CSA and UL certificate of suitability	T4, FM16US0205X UL 60950-1 E115352, CSA C22.2 No. 60950-1 No No Yes No
for safety / from CSA and UL certificate of suitability	T4, FM16US0205X UL 60950-1 E115352, CSA C22.2 No. 60950-1 No No Yes No
for safety / from CSA and UL certificate of suitability	T4, FM16US0205X UL 60950-1 E115352, CSA C22.2 No. 60950-1 No No Yes No
for safety / from CSA and UL certificate of suitability EC Declaration of Conformity CE marking C-Tick E1 approval railway application in accordance with EN 50155 NEMA TS2 IEC 61375 IEC 61850-3 NEMA4X Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af Power-over-Ethernet according to IEEE802.3at for type 2 standard for wireless communication IEEE 802.11a	T4, FM16US0205X UL 60950-1 E115352, CSA C22.2 No. 60950-1 No No Yes No
for safety / from CSA and UL certificate of suitability	T4, FM16US0205X UL 60950-1 E115352, CSA C22.2 No. 60950-1 No No Yes No
for safety / from CSA and UL certificate of suitability	T4, FM16US0205X UL 60950-1 E115352, CSA C22.2 No. 60950-1 No
for safety / from CSA and UL certificate of suitability EC Declaration of Conformity CE marking C-Tick E1 approval railway application in accordance with EN 50155 NEMA TS2 IEC 61375 IEC 61850-3 NEMA4X Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af Power-over-Ethernet according to IEEE802.3at for type 2 standard for wireless communication IEEE 802.11a IEEE 802.11b IEEE 802.11e IEEE 802.11g	T4, FM16US0205X UL 60950-1 E115352, CSA C22.2 No. 60950-1 No
for safety / from CSA and UL certificate of suitability EC Declaration of Conformity CE marking C-Tick E1 approval railway application in accordance with EN 50155 NEMA TS2 IEC 61375 IEC 61850-3 NEMA4X Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af Power-over-Ethernet according to IEEE802.3at for type 2 standard for wireless communication IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11h	T4, FM16US0205X UL 60950-1 E115352, CSA C22.2 No. 60950-1 No Yes Yes Yes Yes Yes Yes

reference code		
reference code • according to IEC 81346-2:2019	KF	=
standards, specifications, approvals / marine cla		
Marine classification association		
American Bureau of Shipping Europe Ltd. (a)	ABS) No	
French marine classification society (BV)	No	
DNV GL	No	
Korean Register of Shipping (KRS)	No.	
Lloyds Register of Shipping (LRS)	No.	
Nippon Kaiji Kyokai (NK)	No	
Polski Rejestr Statkow (PRS)	No.	
Royal Institution of Naval Architects (RINA)	No.	
standards, specifications, approvals / hazardous		
standard / for hazardous zone		60070 15:2005 EN 60070 0:2006 II 2 C Ev pA II TA KEMA 07 ATEV
	014	60079-15:2005, EN 60079-0:2006, II 3 G Ex nA II T4 KEMA 07 ATEX
from CSA and UL	В, (SI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480
standards, specifications, approvals / Environme		
Environmental Product Declaration	Yes	5
global warming potential [CO2 eq]		
• total	200).91 kg
 during manufacturing 	12.	97 kg
during operation	187	7.77 kg
after end of life	0.1	7 kg
accessories		
accessories	24	V DC screw terminal included in scope of delivery
further information / internet links		
internet link		
 to website: Selection guide for cables and c 	onnectors <u>httr</u>	os://support.industry.siemens.com/cs/ww/en/view/109766358
 to web page: selection aid TIA Selection To 	ol <u>httr</u>	os://www.siemens.com/tstcloud
to web page: WLAN country approval		os://www.siemens.com/wireless-approvals
to the website: IWLAN		os://www.siemens.com/iwlan
 to website: Industrial communication 	<u>httr</u>	os://www.siemens.com/simatic-net
to web page: SiePortal	<u>httr</u>	os://sieportal.siemens.com/
to website: Image database	<u>httr</u>	os://www.automation.siemens.com/bilddb
to website: CAx-Download-Manager	<u>httr</u>	os://www.siemens.com/cax
to website: Industry Online Support	<u>httr</u>	os://support.industry.siemens.com
security information		
security information	that In a In	mens provides products and solutions with industrial cybersecurity functions to support the secure operation of plants, systems, machines and networks order to protect plants, systems, machines and networks against cyber eats, it is necessary to implement – and continuously maintain – a holistic, te-of-the-art industrial cybersecurity concept. Siemens' products and utions constitute one element of such a concept. Customers are responsible preventing unauthorized access to their plants, systems, machines and works. Such systems, machines and components should only be connected an enterprise network or the internet if and to the extent such a connection is sessary and only when appropriate security measures (e.g. firewalls and/or work segmentation) are in place. For additional information on industrial persecurity measures that may be implemented, please visit we siemens.com/cybersecurity-industry. Siemens' products and solutions dergo continuous development to make them more secure. Siemens strongly dommends that product updates are applied as soon as they are available at that the latest product versions are used. Use of product versions that are longer supported, and failure to apply the latest updates may increase stomer's exposure to cyber threats. To stay informed about product updates, asscribe to the Siemens Industrial Cybersecurity RSS Feed under assistance.
Approvals / Certificates		
General Product Approval	For use in hazard- ous locations	Radio Equipment Type Approval Certificate



Declaration of Conformity

CCC-Ex

Miscellaneous

last modified: 2/18/2025 **௴**