SIEMENS

Data sheet

6GK5774-1FX00-0AC0

product type designation



W774-1 RJ45 (ISR)

IWLAN Access Point, SCALANCE W774-1 RJ45, 1 radio, 2 R-SMA antenna port, iFeatures support via KEY-PLUG, IEEE 802.11a/b/g/h/n, 2.4/5GHz, gross data rate 300 Mbit/s, 2x RJ45 max. 100 Mbit/s, PoE integrated 2-port switch, redundant 24 V DC, joint block, IP30, -20... 60 °C, plug slot WPA2/802.11i/e, observe national approvals! CERT ID: MSN-W1-RJ-E2, scope of delivery: Manuals on CD-ROM, German/English, 1x joint block; for operation in Israel.

transfer rate	
transfer rate	
with WLAN / maximum	300 Mbit/s
for Industrial Ethernet	10, 100 Mbit/s
transfer rate / for Industrial Ethernet	
• minimum	10 Mbit/s
• maximum	100 Mbit/s
interfaces	
number of electrical connections	
 for network components or terminal equipment 	2
 for power supply 	1
 for redundant voltage supply 	1
type of electrical connection	
 for network components or terminal equipment 	RJ45 socket
 for power supply 	4-pole screw terminal, PoE
memory	
design of the removable storage	
• C-PLUG	Yes
• KEY-PLUG	Yes
interfaces / wireless	
number of radio cards / permanently installed	1
transmission mode / for multiple input multiple output (MIMO)	2x2
number of spatial streams	2
number of electrical connections / for external antenna(s)	2
type of electrical connection / for external antenna(s)	R-SMA (socket)
product feature / external antenna can be mounted directly on device	Yes
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage	
 from Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af 	48 V
consumed current	
• at DC / at 24 V / typical	0.25 A
 with Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af / typical 	0.125 A
power loss [W]	
• at DC / at 24 V / typical	6 W
 with Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af / typical 	6 W

supply voltage / 1	10.21/	
• from terminal block	19.2 V	
supply voltage / 2	20.0.1/	
from terminal block	28.8 V	
ambient conditions		
ambient temperature		
during operation	-20 +60 °C	
during storage	-40 +85 °C	
during transport	-40 +85 °C	
relative humidity / at 25 °C / without condensation / during operation / maximum	97 %	
ambient condition / for operation	When used under hazardous conditions (Zone 2), the SCALANCE W774-1 RJ45 or W734-1 RJ45 product must be installed in an enclosure. To comply with EN 50021, this enclosure must meet the requirements of at least IP 54 in compliance with EN 60529.	
protection class IP	IP30	
design, dimensions and weights		
width	26 mm	
height	156 mm	
depth	127 mm	
width / of the enclosure / without antenna	26 mm	
height / of the enclosure / without antenna	147 mm	
depth / of the enclosure / without antenna	127 mm	
net weight	0.52 kg	
fastening method	wall mounting only if flat mounted	
S7-300 rail mounting	Yes	
S7-1500 rail mounting	Yes	
35 mm DIN-rail mounting	Yes	
C C	Yes	
wall mounting radio frequencies		
operating frequency		
for WLAN in 2.4 GHz frequency band	2.41 2.48 GHz; depending on the country approvals	
• for WLAN in 5 GHz frequency band	4.9 5.8 GHz; depending on the country approvals	
product features, product functions, product components / gen		
product function / Access Point Mode	Yes	
product function / client Mode	Yes	
number of SSIDs	4	
product function	Very Only in combination with the WEV DULIO MIZOCIE.	
iPCF Access Point	Yes; Only in combination with the 'KEY-PLUG W780 iFeatures'	
• iPCF client	Yes; Only in combination with the 'KEY-PLUG W740 iFeatures'	
iPCF-MC Access Point	No	
iPCF-MC client	Yes; Only in combination with the 'KEY-PLUG W740 iFeatures'	
number of iPCF-capable radio modules	1	
product function / iREF	Yes; Only in combination with the 'KEY-PLUG W780 iFeatures' or 'KEY-PLUG W740 iFeatures'	
number of iREF-capable radio modules	1	
product function / iPRP	Yes; In combination with the 'KEY-PLUG W780 iFeatures' only	
product functions / management, configuration, engineering		
number of manageable IP addresses / in client	8	
product function		
• CLI	Yes	
 web-based management 	Yes	
MIB support	Yes	
• TRAPs via email	Yes	
configuration with STEP 7	Yes	
 configuration with STEP 7 in the TIA Portal 	Yes	
operation with IWLAN controller	No	
operation with Enterasys WLAN controller	No	
forced roaming on IP down with IWLAN	Yes	
forced roaming on link down with IWLAN	Yes	
WDS	Yes	
protocol / is supported		

 Address Resolution Protocol (ARP) 	Yes
• ICMP	Yes
• Telnet	Yes
• HTTP	Yes
• HTTPS	Yes
• TFTP	Yes
• DCP	Yes
• LLDP	Yes
identification & maintenance function	
 I&M0 - device-specific information 	Yes
 I&M1 - higher level designation/location designation 	Yes
product function / is supported / identification link	Yes; acc. to IEC 61406-1:2022
product functions / diagnostics	
product function	
PROFINET IO diagnosis	Yes
 link check 	No
connection monitoring IP-Alive	No
 localization via Aeroscout 	Yes
• SysLog	Yes
protocol / is supported	
SNMP v1	Yes
• SNMP v2	Yes
• SNMP v3	Yes
product functions / VLAN	
product function	
function VLAN with IWLAN	Yes
product functions / DHCP	1 es
product function	
DHCP client	Yes
• DHCP server	Yes
DHCP Option 82	Yes
product functions / redundancy	
protocol / is supported	
• STP/RSTP	Yes
• MSTP	Yes
• RSTP	Yes
product functions / security	
product function	
ACL - MAC-based	Yes
 management security, ACL-IP based 	Yes
• IEEE 802.1x (radius)	Yes
• NAT/NAPT	Yes
 access protection according to IEEE802.11i 	Yes
WPA/WPA2	Yes
• TKIP/AES	Yes
protocol / is supported	
• SSH	Yes
RADIUS	Yes
product functions / time	
protocol / is supported	
• NTP	Yes
• SNTP	Yes
 SIMATIC time synchronization (SIMATIC Time) 	Yes
standards, specifications, approvals	
standard	
• for FM	FM 3611: Class I, Division 2, Groups A,B,C,D, T4 / Class 1, Zone 2, Group IIC, T4, FM16US0205X
 for safety / from CSA and UL 	UL 60950-1 E115352, CSA C22.2 No. 60950-1
certificate of suitability	
• EC Declaration of Conformity	No
• CE marking	No

C-Tick	Yes	
 E1 approval 	No	
 railway application in accordance with EN 50155 	No	
 railway application in accordance with EN 50121-4 	No	
NEMA TS2	No	
• IEC 61375	No	
• IEC 61850-3	No	
• NEMA4X	No	
 Power-over-Ethernet according IEEE802.3at for type 1 and IEEE802.3af 	Yes	
 Power-over-Ethernet according to IEEE802.3at for type 2 	Yes	
standard for wireless communication		
• IEEE 802.11a	Yes	
• IEEE 802.11b	Yes	
• IEEE 802.11e	Yes	
• IEEE 802.11g	Yes	
• IEEE 802.11h	Yes	
• IEEE 802.11i	Yes	
• IEEE 802.11n	Yes	
wireless approval	You will find the current list of countries at: www.siemens.de/funkzulassungen	
reference code		
 according to IEC 81346-2:2019 	KFE	
standards, specifications, approvals / marine classification		
Marine classification association		
American Bureau of Shipping Europe Ltd. (ABS)	Yes	
French marine classification society (BV)	Yes	
• DNV GL	Yes	
 Korean Register of Shipping (KRS) 	Yes	
Lloyds Register of Shipping (LRS)	Yes	
Nippon Kaiji Kyokai (NK)	Yes	
Polski Rejestr Statkow (PRS)	Yes	
Royal Institution of Naval Architects (RINA)	Yes	
standards, specifications, approvals / hazardous environments		
standard / for hazardous zone	EN 60079-15:2005, EN 60079-0:2006, II 3 G Ex nA II T4 KEMA 07 ATEX	
	0145X	
• from CSA and UL	0145X ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480	
from CSA and UL certificate of suitability / CCC / for hazardous zone according to GB standard	0145X ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480 Yes; GB3836.1, GB3836.8	
 from CSA and UL certificate of suitability / CCC / for hazardous zone according to GB standard as marking 	0145X ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480 Yes; GB3836.1, GB3836.8 Ex nA IIC T4 Gc	
from CSA and UL certificate of suitability / CCC / for hazardous zone according to GB standard e as marking standards, specifications, approvals / Environmental Product D	0145X ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480 Yes; GB3836.1, GB3836.8 Ex nA IIC T4 Gc eclaration	
from CSA and UL certificate of suitability / CCC / for hazardous zone according to GB standard as marking standards, specifications, approvals / Environmental Product D Environmental Product Declaration 	0145X ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480 Yes; GB3836.1, GB3836.8 Ex nA IIC T4 Gc	
from CSA and UL certificate of suitability / CCC / for hazardous zone according to GB standard • as marking standards, specifications, approvals / Environmental Product D Environmental Product Declaration global warming potential [CO2 eq]	0145X ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480 Yes; GB3836.1, GB3836.8 Ex nA IIC T4 Gc eclaration Yes	
 from CSA and UL certificate of suitability / CCC / for hazardous zone according to GB standard as marking standards, specifications, approvals / Environmental Product D Environmental Product Declaration global warming potential [CO2 eq] total 	0145X ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480 Yes; GB3836.1, GB3836.8 Ex nA IIC T4 Gc eclaration Yes 195.92 kg	
 from CSA and UL certificate of suitability / CCC / for hazardous zone according to GB standard as marking standards, specifications, approvals / Environmental Product D Environmental Product Declaration global warming potential [CO2 eq] total during manufacturing 	0145X ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480 Yes; GB3836.1, GB3836.8 Ex nA IIC T4 Gc eclaration Yes 195.92 kg 29.7 kg	
 from CSA and UL certificate of suitability / CCC / for hazardous zone according to GB standard as marking standards, specifications, approvals / Environmental Product D Environmental Product Declaration global warming potential [CO2 eq] total during manufacturing during operation 	0145X ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480 Yes; GB3836.1, GB3836.8 Ex nA IIC T4 Gc eclaration Yes 195.92 kg	
 from CSA and UL certificate of suitability / CCC / for hazardous zone according to GB standard as marking standards, specifications, approvals / Environmental Product D Environmental Product Declaration global warming potential [CO2 eq] total during manufacturing during operation after end of life 	0145X ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480 Yes; GB3836.1, GB3836.8 Ex nA IIC T4 Gc eclaration Yes 195.92 kg 29.7 kg	
 from CSA and UL certificate of suitability / CCC / for hazardous zone according to GB standard as marking standards, specifications, approvals / Environmental Product D Environmental Product Declaration global warming potential [CO2 eq] total during manufacturing during operation 	0145X ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480 Yes; GB3836.1, GB3836.8 Ex nA IIC T4 Gc eclaration Yes 195.92 kg 29.7 kg 166.06 kg	
 from CSA and UL certificate of suitability / CCC / for hazardous zone according to GB standard as marking standards, specifications, approvals / Environmental Product D Environmental Product Declaration global warming potential [CO2 eq] total during manufacturing during operation after end of life 	0145X ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480 Yes; GB3836.1, GB3836.8 Ex nA IIC T4 Gc eclaration Yes 195.92 kg 29.7 kg 166.06 kg	
 from CSA and UL certificate of suitability / CCC / for hazardous zone according to GB standard as marking standards, specifications, approvals / Environmental Product D Environmental Product Declaration global warming potential [CO2 eq] total during manufacturing during operation after end of life accessories 	0145X ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480 Yes; GB3836.1, GB3836.8 Ex nA IIC T4 Gc eclaration Yes 195.92 kg 29.7 kg 166.06 kg 0.16 kg	
 from CSA and UL certificate of suitability / CCC / for hazardous zone according to GB standard as marking standards, specifications, approvals / Environmental Product D Environmental Product Declaration global warming potential [CO2 eq] total during manufacturing during operation after end of life accessories 	0145X ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480 Yes; GB3836.1, GB3836.8 Ex nA IIC T4 Gc eclaration Yes 195.92 kg 29.7 kg 166.06 kg 0.16 kg	
 from CSA and UL certificate of suitability / CCC / for hazardous zone according to GB standard as marking standards, specifications, approvals / Environmental Product D Environmental Product Declaration global warming potential [CO2 eq] total during manufacturing during operation after end of life accessories further information / internet links 	0145X ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480 Yes; GB3836.1, GB3836.8 Ex nA IIC T4 Gc eclaration Yes 195.92 kg 29.7 kg 166.06 kg 0.16 kg	
 from CSA and UL certificate of suitability / CCC / for hazardous zone according to GB standard as marking standards, specifications, approvals / Environmental Product D Environmental Product Declaration global warming potential [CO2 eq] total during manufacturing during operation after end of life accessories further information / internet links internet link 	0145X ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480 Yes; GB3836.1, GB3836.8 Ex nA IIC T4 Gc eclaration Yes 195.92 kg 29.7 kg 166.06 kg 0.16 kg 24 V DC screw terminal included in scope of delivery	
 from CSA and UL certificate of suitability / CCC / for hazardous zone according to GB standard as marking standards, specifications, approvals / Environmental Product D Environmental Product Declaration global warming potential [CO2 eq] total during manufacturing during operation after end of life accessories further information / internet links internet link to website: Selection guide for cables and connectors 	0145X ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480 Yes; GB3836.1, GB3836.8 Ex nA IIC T4 Gc eclaration Yes 195.92 kg 29.7 kg 166.06 kg 0.16 kg 24 V DC screw terminal included in scope of delivery https://support.industry.siemens.com/cs/ww/en/view/109766358	
 from CSA and UL certificate of suitability / CCC / for hazardous zone according to GB standard as marking standards, specifications, approvals / Environmental Product D Environmental Product Declaration global warming potential [CO2 eq] total during manufacturing during operation after end of life accessories further information / internet links internet link to website: Selection guide for cables and connectors to web page: selection aid TIA Selection Tool 	0145X ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480 Yes; GB3836.1, GB3836.8 Ex nA IIC T4 Gc eclaration Yes 195.92 kg 29.7 kg 166.06 kg 0.16 kg 24 V DC screw terminal included in scope of delivery https://support.industry.siemens.com/cs/ww/en/view/109766358 https://www.siemens.com/tstcloud	
 from CSA and UL certificate of suitability / CCC / for hazardous zone according to GB standard as marking standards, specifications, approvals / Environmental Product D Environmental Product Declaration global warming potential [CO2 eq] total during manufacturing during operation after end of life accessories accessories further information / internet links internet link to website: Selection guide for cables and connectors to web page: selection aid TIA Selection Tool to web page: WLAN country approval 	0145X ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480 Yes; GB3836.1, GB3836.8 Ex nA IIC T4 Gc eclaration Yes 195.92 kg 29.7 kg 166.06 kg 0.16 kg 24 V DC screw terminal included in scope of delivery 24 V DC screw terminal included in scope of delivery	
 from CSA and UL certificate of suitability / CCC / for hazardous zone according to GB standard as marking standards, specifications, approvals / Environmental Product D Environmental Product Declaration global warming potential [CO2 eq] total during manufacturing during operation after end of life accessories further information / internet links internet link to web page: selection guide for cables and connectors to web page: WLAN country approval to the website: IWLAN 	0145X ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480 Yes; GB3836.1, GB3836.8 Ex nA IIC T4 Gc eclaration Yes 195.92 kg 29.7 kg 166.06 kg 0.16 kg 24 V DC screw terminal included in scope of delivery https://support.industry.siemens.com/cs/ww/en/view/109766358 https://www.siemens.com/tstcloud https://www.siemens.com/tstcloud	
 from CSA and UL certificate of suitability / CCC / for hazardous zone according to GB standard as marking standards, specifications, approvals / Environmental Product D Environmental Product Declaration global warming potential [CO2 eq] total during manufacturing during operation after end of life accessories further information / internet links internet link to web page: selection guide for cables and connectors to web page: WLAN country approval to the website: IWLAN to website: Industrial communication 	0145X ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480 Yes; GB3836.1, GB3836.8 Ex nA IIC T4 Gc eclaration Yes 195.92 kg 29.7 kg 166.06 kg 0.16 kg 24 V DC screw terminal included in scope of delivery https://support.industry.siemens.com/cs/ww/en/view/109766358 https://www.siemens.com/tstcloud https://www.siemens.com/wireless-approvals https://www.siemens.com/wireless-approvals https://www.siemens.com/wireless-approvals	
 from CSA and UL certificate of suitability / CCC / for hazardous zone according to GB standard as marking standards, specifications, approvals / Environmental Product D Environmental Product Declaration global warming potential [CO2 eq] total during manufacturing during operation after end of life accessories further information / internet links internet link to web page: selection guide for cables and connectors to web page: selection aid TIA Selection Tool to web page: WLAN country approval to the website: IWLAN to website: Industrial communication to web page: SiePortal 	0145X ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480 Yes; GB3836.1, GB3836.8 Ex nA IIC T4 Gc eclaration Yes 195.92 kg 29.7 kg 166.06 kg 0.16 kg 24 V DC screw terminal included in scope of delivery https://support.industry.siemens.com/cs/ww/en/view/109766358 https://www.siemens.com/tstcloud https://www.siemens.com/tstcloud https://www.siemens.com/iwless-approvals https://www.siemens.com/iwlan https://www.siemens.com/simatic-net https://sieportal.siemens.com/	
 from CSA and UL certificate of suitability / CCC / for hazardous zone according to GB standard as marking standards, specifications, approvals / Environmental Product D Environmental Product Declaration global warming potential [CO2 eq] total during manufacturing during operation after end of life accessories further information / internet links internet link to website: Selection guide for cables and connectors to web page: selection aid TIA Selection Tool to web page: WLAN country approval to the website: IWLAN to web page: SiePortal to web page: SiePortal to website: Image database 	0145X ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480 Yes; GB3836.1, GB3836.8 Ex nA IIC T4 Gc eclaration Yes 195.92 kg 29.7 kg 166.06 kg 0.16 kg 24 V DC screw terminal included in scope of delivery https://support.industry.siemens.com/cs/ww/en/view/109766358 https://www.siemens.com/tstcloud https://www.siemens.com/tstcloud https://www.siemens.com/iwless-approvals https://www.siemens.com/iwlan https://www.siemens.com/iwlan https://www.siemens.com/iwlan https://www.automation.siemens.com/bilddb	
 from CSA and UL certificate of suitability / CCC / for hazardous zone according to GB standard as marking standards, specifications, approvals / Environmental Product D Environmental Product Declaration global warming potential [CO2 eq] total during manufacturing during operation after end of life accessories further information / internet links internet link to website: Selection guide for cables and connectors to web page: selection aid TIA Selection Tool to web page: WLAN country approval to the website: IWLAN to website: Industrial communication to web page: SiePortal to website: Image database to website: CAx-Download-Manager 	0145X ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480 Yes; GB3836.1, GB3836.8 Ex nA IIC T4 Gc eclaration Yes 195.92 kg 29.7 kg 166.06 kg 0.16 kg 24 V DC screw terminal included in scope of delivery https://support.industry.siemens.com/cs/ww/en/view/109766358 https://www.siemens.com/tstcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud	
 from CSA and UL certificate of suitability / CCC / for hazardous zone according to GB standard as marking standards, specifications, approvals / Environmental Product D Environmental Product Declaration global warming potential [CO2 eq] total during manufacturing during operation after end of life accessories further information / internet links internet link to website: Selection guide for cables and connectors to web page: wLAN country approval to the website: INULAN to website: Industrial communication to website: Image database to website: CAx-Download-Manager to website: Industry Online Support 	0145X ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480 Yes; GB3836.1, GB3836.8 Ex nA IIC T4 Gc eclaration Yes 195.92 kg 29.7 kg 166.06 kg 0.16 kg 24 V DC screw terminal included in scope of delivery https://support.industry.siemens.com/cs/ww/en/view/109766358 https://www.siemens.com/tstcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud https://www.siemens.com/istcloud	

Subject to change without notice © Copyright Siemens that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement - and continuously maintain - a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

Approvals / Certificates			
General Product Approval	For use in hazard- ous locations	Radio Equipment Type Approval Certificate	
Declaration of Con- formity	<u>CCC-Ex</u>	Miscellaneous	

last modified:

2/8/2025 🖸