

product type designation

product description

Fiber optic standard cable

Flexible glass fiber-optic cable, preferred length, preassembled

fiber optic cable (62.5/125), standard cable, splittable, pre-assembled with 4 BFOC connectors, length 4 m.



suitability for use

Cable for installation indoors and outdoors

version of the assembled FO cable

Assembled with four BFOC connectors

cable designation

AT-V(ZN)YY 2X1 G 62,5/125 OM1

wire length

4 m

optical data

attenuation factor per length

- at 850 nm / maximum
- at 1300 nm / maximum

3 dB/km
0.8 dB/km

bandwidth length product

- at 850 nm
- at 1300 nm

300 GHz·m
800 GHz·m

mechanical data

number of fibers / per FOC core

1

number of FO cores / per FOC cable

2

version of the FO conductor fiber

Multimode graded-index fiber 62.5/125 µm, OM 1

design of the FOC core

Compact core, diameter 900 µm

design of the fiber-optic cable

Segmentable outer conductor

outer diameter

- of the optical fibers
- of the optical fiber sheath
- of the FOC core sheath

62.5 µm
125 µm
3.5 mm

width / of cable sheath

9.8 mm

thickness / of cable sheath

6.3 mm

material

- of the fiber-optic cable core
- of the optical fiber sheath
- of the FOC core sheath
- of the fiber-optic cable sheath
- of the strain relief

Quartz glass
Quartz glass
PVC
PVC
Aramid fibers and glass roving

color

- of the FOC core sheath
- of cable sheath

gray
Black

bending radius

- with single bend / minimum permissible
- with multiple bends / minimum permissible

80 mm
80 mm

tensile load

- during installation / short-term
- during operation / maximum

1500 N
1500 N

| | |
|--|---|
| continuous shear force per length | 150 N/cm |
| weight per length | 70 kg/km |
| ambient conditions | |
| ambient temperature | |
| • during operation | -40 ... +85 °C |
| • during storage | -40 ... +85 °C |
| • during transport | -40 ... +85 °C |
| • during installation | -5 ... +50 °C |
| fire behavior | flame-resistant acc. to IEC 60332-1-2 and IEC 60332-3-22 (Cat. A) |
| chemical resistance | |
| • to mineral oil | not resistant |
| • to grease | not resistant |
| radiological resistance / to UV radiation | resistant |
| protection class IP | IP20 |
| product features, product functions, product components / general | |
| product feature | |
| • halogen-free | No |
| • silicon-free | Yes |
| product component / rodent protection | No |
| wire length | |
| • for glass FOC / for 100BaseFX / for Industrial Ethernet / maximum | 4000 m |
| • for glass FOC / for 1000BaseSX / for Industrial Ethernet / maximum | 500 m |
| • for glass FOC / for 1000BaseLX / for Industrial Ethernet / maximum | 1000 m |
| • for glass FOC / with PROFIBUS / maximum | 3000 m |
| standards, specifications, approvals | |
| certificate of suitability | |
| • RoHS conformity | Yes |
| reference code | |
| • according to IEC 81346-2 | WH |
| • according to IEC 81346-2:2019 | WHA |
| further information / internet links | |
| internet link | |
| • to website: Selection guide for cables and connectors | https://support.industry.siemens.com/cs/ww/en/view/109766358 |
| • to web page: selection aid TIA Selection Tool | https://www.siemens.com/tstcloud |
| • to website: Industrial communication | https://www.siemens.com/simatic-net |
| • to web page: SiePortal | https://sieportal.siemens.com/ |
| • to website: Image database | https://www.automation.siemens.com/bilddb |
| • to website: CAX-Download-Manager | https://www.siemens.com/cax |
| • to website: Industry Online Support | https://support.industry.siemens.com |
| security information / header | |
| security information | Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry . Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert . (V4.7) |
| Approvals / Certificates | |
| General Product Approval | |





[Declaration of Con-
formity](#)



[Manufacturer Declara-
tion](#)



| General Product Ap- proval | Marine / Shipping | other | Environment |
|--|---|------------------------------|------------------------------|
|  RCM |  | Confirmation | Confirmation |

last modified:

8/9/2024 