

**product type designation**

product description

**Fiber optic standard cable**

Flexible glass fiber-optic cable, preferred length, preassembled

fiber optic cable (62.5/125), standard cable, splittable, pre-assembled with 4 BFOC connectors, length 60 m.



suitability for use	Cable for installation indoors and outdoors
version of the assembled FO cable	Assembled with four BFOC connectors
cable designation	AT-V(ZN)YY 2X1 G 62,5/125 OM1
wire length	60 m

**optical data**

attenuation factor per length	
<ul style="list-style-type: none"> <li>at 850 nm / maximum</li> <li>at 1300 nm / maximum</li> </ul>	3 dB/km 0.8 dB/km
bandwidth length product	
<ul style="list-style-type: none"> <li>at 850 nm</li> <li>at 1300 nm</li> </ul>	300 GHz·m 800 GHz·m

**mechanical data**

number of fibers / per FOC core	1
number of FO cores / per FOC cable	2
version of the FO conductor fiber	Multimode graded-index fiber 62.5/125 µm, OM 1
design of the FOC core	Compact core, diameter 900 µm
design of the fiber-optic cable	Segmentable outer conductor
outer diameter	
<ul style="list-style-type: none"> <li>of the optical fibers</li> <li>of the optical fiber sheath</li> <li>of the FOC core sheath</li> </ul>	62.5 µm 125 µm 3.5 mm
width / of cable sheath	9.8 mm
thickness / of cable sheath	6.3 mm
material	
<ul style="list-style-type: none"> <li>of the fiber-optic cable core</li> <li>of the optical fiber sheath</li> <li>of the FOC core sheath</li> <li>of the fiber-optic cable sheath</li> <li>of the strain relief</li> </ul>	Quartz glass Quartz glass PVC PVC Aramid fibers and glass roving
color	
<ul style="list-style-type: none"> <li>of the FOC core sheath</li> <li>of cable sheath</li> </ul>	gray Black
bending radius	
<ul style="list-style-type: none"> <li>with single bend / minimum permissible</li> <li>with multiple bends / minimum permissible</li> </ul>	80 mm 80 mm
tensile load	
<ul style="list-style-type: none"> <li>during installation / short-term</li> <li>during operation / maximum</li> </ul>	1500 N 1500 N



continuous shear force per length	150 N/cm
weight per length	70 kg/km
<b>ambient conditions</b>	
ambient temperature	
• during operation	-40 ... +85 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
• during installation	-5 ... +50 °C
fire behavior	flame-resistant acc. to IEC 60332-1-2 and IEC 60332-3-22 (Cat. A)
chemical resistance	
• to mineral oil	not resistant
• to grease	not resistant
radiological resistance / to UV radiation	resistant
protection class IP	IP20
<b>product features, product functions, product components / general</b>	
product feature	
• halogen-free	No
• silicon-free	Yes
product component / rodent protection	No
wire length	
• for glass FOC / for 100BaseFX / for Industrial Ethernet / maximum	4000 m
• for glass FOC / for 1000BaseSX / for Industrial Ethernet / maximum	500 m
• for glass FOC / for 1000BaseLX / for Industrial Ethernet / maximum	1000 m
• for glass FOC / with PROFIBUS / maximum	3000 m
<b>standards, specifications, approvals</b>	
certificate of suitability	
• RoHS conformity	Yes
reference code	
• according to IEC 81346-2	WH
• according to IEC 81346-2:2019	WHA
<b>further information / internet links</b>	
internet link	
• to website: Selection guide for cables and connectors	<a href="https://support.industry.siemens.com/cs/ww/en/view/109766358">https://support.industry.siemens.com/cs/ww/en/view/109766358</a>
• to web page: selection aid TIA Selection Tool	<a href="https://www.siemens.com/tstcloud">https://www.siemens.com/tstcloud</a>
• to website: Industrial communication	<a href="https://www.siemens.com/simatic-net">https://www.siemens.com/simatic-net</a>
• to web page: SiePortal	<a href="https://sieportal.siemens.com/">https://sieportal.siemens.com/</a>
• to website: Image database	<a href="https://www.automation.siemens.com/bilddb">https://www.automation.siemens.com/bilddb</a>
• to website: CAx-Download-Manager	<a href="https://www.siemens.com/cax">https://www.siemens.com/cax</a>
• to website: Industry Online Support	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>security information / header</b>	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit <a href="http://www.siemens.com/cybersecurity-industry">www.siemens.com/cybersecurity-industry</a> . Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <a href="https://www.siemens.com/cert.">https://www.siemens.com/cert.</a> (V4.7)
<b>Approvals / Certificates</b>	
<b>General Product Approval</b>	



[Declaration of Con-  
formity](#)

[Manufacturer Declara-  
tion](#)



General Product Ap- proval	Marine / Shipping	other	Environment
 RCM		<a href="#">Confirmation</a>	<a href="#">Confirmation</a>

last modified:

8/9/2024 