# **SIEMENS**

## Data sheet

## 6XV1843-5FH10-0CB0

## product type designation

product description



Figure similar

### SM FO CORD SC/BFOC, 9/125

Singlemode glass fiber-optic cable, preassembled

SM FO Cord SC/BFOC; 9/125, pre-assembled with 1x SC duplex connectors and 1x, BFOC connectors; length 1.0 m.

| Figuresimilar  |  |
|--|--|
| suitability for use                                  | Cable for applications in the control cabinet                    |
| version of the assembled FO cable                    | Pre-assembled with 1x SC DUPLEX connector and 2x, BFOC connector |
| cable designation                                    | I-V(ZN)H 2E9/125 G.652D  |
| wire length  | 1 m  |
| optical data   |  |
| attenuation factor per length                        |  |
| • at 1300 nm / maximum                               | 0.4 dB/km  |
| • at 1550 nm / maximum                               | 0.3 dB/km  |
| mechanical data                                      |  |
| number of fibers / per FOC core                      | 1  |
| number of FO cores / per FOC cable                   | 2  |
| version of the FO conductor fiber                    | Singlemode glass fiber 9/125 μm                                  |
| design of the FOC core                               | Fixed core   |
| outer diameter                                       |  |
| <ul> <li>of the optical fibers</li> </ul>            | 9 μm   |
| <ul> <li>of the optical fiber sheath</li> </ul>      | 125 μm   |
| of the FOC core sheath                               | 2.8 mm   |
| width / of cable sheath                              | 5.9 mm   |
| thickness / of cable sheath                          | 2.8 mm   |
| material   |  |
| <ul> <li>of the fiber-optic cable core</li> </ul>    | Quartz glass   |
| <ul> <li>of the optical fiber sheath</li> </ul>      | Quartz glass   |
| <ul> <li>of the FOC core sheath</li> </ul>           | FR-LSZH  |
| <ul> <li>of the fiber-optic cable sheath</li> </ul>  | LSZH   |
| of the strain relief                                 | Aramid fibers  |
| color  |  |
| of the FOC core sheath                               | green/green  |
| bending radius                                       |  |
| with single bend / minimum permissible               | 42 mm  |
| tensile load   |  |
| <ul> <li>during installation / short-term</li> </ul> | 500 N  |
| during operation / maximum                           | 500 N  |
| continuous shear force per length                    | 100 N/cm   |
| ambient conditions                                   |  |
| ambient temperature                                  |  |
| <ul><li>during operation</li></ul>                   | -30 +70 °C   |
| during storage                                       | -30 +70 °C   |

| during transport  | -30 +70 °C   |
|---|--|
| during installation   | -5 +50 °C  |
| fire behavior   | flame-resistant acc. to IEC 60332-3-22 (Cat. A)  |
| protection class IP   | IP20   |
| product features, product functions, product components / gen     | eral   |
| product feature   |  |
| <ul><li>halogen-free</li></ul>                                    | Yes  |
| • silicon-free  | Yes  |
| product component / rodent protection                             | No   |
| standards, specifications, approvals                              |  |
| certificate of suitability  |  |
| RoHS conformity   | Yes  |
| reference code  |  |
| <ul> <li>according to IEC 81346-2</li> </ul>                      | WH   |
| <ul> <li>according to IEC 81346-2:2019</li> </ul>                 | WHA  |
| further information / internet links                              |  |
| internet link   |  |
| • to website: Selection guide for cables and connectors           | https://support.industry.siemens.com/cs/ww/en/view/109766358   |
| <ul> <li>to web page: selection aid TIA Selection Tool</li> </ul> | https://www.siemens.com/tstcloud   |
| <ul> <li>to website: Industrial communication</li> </ul>          | https://www.siemens.com/simatic-net  |
| • to web page: SiePortal  | https://sieportal.siemens.com/   |
| <ul><li>to website: Image database</li></ul>                      | https://www.automation.siemens.com/bilddb  |
| <ul><li>to website: CAx-Download-Manager</li></ul>                | https://www.siemens.com/cax  |
| • to website: Industry Online Support                             | https://support.industry.siemens.com   |
| security information / header                                     |  |
| security information  | Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. |

state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under

In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic,

#### Approvals / Certificates

**General Product Approval** 

**Environment** 



Declaration of Conformity





https://www.siemens.com/cert. (V4.7)

Manufacturer Declaration Confirmation

| Industrial Con | nmunication |
|----------------|-------------|
|----------------|-------------|

**PROFINET** 

last modified:

8/9/2024