## SIEMENS

## Data sheet

## 6GK1901-1BB20-6AA0

product type designation product description



IE FC RJ45 Plug PRO (Push Pull) RJ45 data connector

IE FC RJ45 plug PRO, IP65 FastConnect push-pull connector for on-site assembly with IE FC TP cable 2x 2; 1 pack = 1 unit.

Field-assembly connector for push-pull device connection in high degree of

suitability for use

protection transfer rate 10 Mbit/s, 100 Mbit/s transfer rate / for Industrial Ethernet interfaces number of electrical connections • for Industrial Ethernet FC TP cables 4 • for network components or terminal equipment 1 type of electrical connection • for Industrial Ethernet FC TP cables integrated cut-and-clamp contacts for 4-wire TP FC installation cable AWG22 · for network components or terminal equipment RJ45 connector (Push Pull device connection) type of electrical connection / FastConnect Yes mechanical data material / of the enclosure plastic number of reuses 10 locking mechanism design Push-pull design, dimensions and weights type of cable outlet 180° cable outlet width 22 mm height 29 mm depth 73 mm 68.8 g net weight 6.5 ... 6.5 mm connectable cable cross-section 0.33 mm<sup>2</sup> connectable conductor cross-section ambient temperature • during operation -40 ... +70 °C -40 ... +70 °C • during storage -40 ... +70 °C during transport chemical resistance • to water resistant protection class IP IP65/67 product features, product functions, product components / genera product feature PoE capability Yes PoE+capability Yes • silicon-free Yes product component

<ul> <li>strain relief</li> </ul>			Yes		
standards, specificatio	ns, approvals				
certificate of suitability					
RoHS conformity			Yes		
UL approval			Yes		
<ul> <li>cULus approval</li> </ul>			No		
<ul> <li>railway application in accordance with EN 50155</li> </ul>			No		
standard for structured cabling			Cat5		
reference code					
according to IEC 81346-2:2019			XGA		
further information / inf	ternet links				
internet link					
• to website: Selection guide for cables and connectors			https://support.industry.siemens.com/cs/ww/en/view/109766358		
• to web page: selection aid TIA Selection Tool			https://www.siemens.com/tstcloud		
• to website: Industrial communication			https://www.siemens.com/simatic-net		
• to web page: SiePortal			https://sieportal.siemens.com		
• to website: Image database			https://www.automation.siemens.com/bilddb		
• to website: CAx-Download-Manager			https://www.siemens.com/cax		
to website: Industry Online Support			https://support.industry.siemens.com		
security information	· · · ·				
			for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)		
Approvals / Certificates	5				
General Product Approval				Test Certificates	Marine / Shipping
Declaration of Con- formity		EHC	<u>Miscellaneous</u>	Special Test Certific- ate	
Marine / Shipping	Environment	Industrial Com	nunication		
Hoyd's Register uis	<u>Confirmation</u>	<u>PROFINET</u>			

last modified:

12/9/2024 🖸