



SIMATIC DP, Electronic module for ET 200 PRO 4 AI U High Feature, ± 10 V; 0...10 V; ± 5 V; 1...5V; Channel diagnostics; incl. bus module, Connection module IO 6ES7194-4..00-0AA0 order separately

Supply voltage	
Rated value (DC)	24 V
Reverse polarity protection	Yes; against destruction
Input current	
from supply voltage 1L+, max.	40 mA; Typical
from backplane bus 3.3 V DC, max.	12 mA; Typical
Encoder supply	
Number of outputs	4
Short-circuit protection	Yes; per module, electronic to frame
Output current	
• up to 55 °C, max.	1 A
Power loss	
Power loss, typ.	1.1 W
Address area	
Address space per module	
• Address space per module, max.	8 byte
Analog inputs	
Number of analog inputs	4
permissible input voltage for voltage input (destruction limit), max.	35 V
Cycle time (all channels) max.	5 ms
Input ranges (rated values), voltages	
• 0 to +10 V	Yes
• 1 V to 5 V	Yes
• -10 V to +10 V	Yes
• -5 V to +5 V	Yes
Cable length	
• shielded, max.	30 m
Analog value generation for the inputs	
Measurement principle	integrating
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	15 bit; 15 bit + sign at ± 10 V, at ± 5 V; 15 bit at 0 V to 10 V, at 1 V to 5 V
• Integration time (ms)	0,3 / 16,7 / 20 / 60
• Interference voltage suppression for interference frequency f_1 in Hz	16,67 / 50 / 60 / 3 600
• Conversion time (per channel)	1.1 ms
Smoothing of measured values	
• parameterizable	Yes
• Step: None	Yes; 1x cycle time
• Step: low	Yes; 4x cycle time

• Step: Medium • Step: High		Yes; 16x cycle time	
		Yes; 64x cycle time	
Encoder			
Connection of signal encoders			
• for voltage measurement	Yes		
Errors/accuracies			
Linearity error (relative to input range), (+/-)	0.0075 %		
Temperature error (relative to input range), (+/-)	0.00075 %/K		
Crosstalk between the inputs, min.	-70 dB		
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.004 %		
Operational error limit in overall temperature range			
• Voltage, relative to input range, (+/-)	0.1 %		
Basic error limit (operational limit at 25 °C)			
• Voltage, relative to input range, (+/-)	0.075 %		
Interference voltage suppression for $f = n \times (f_1 \pm 0.5 \%)$, f_1 = interference frequency			
• Series mode interference (peak value of interference < rated value of input range), min.	60 dB		
• Common mode interference (USS < 2.5 V), min.	80 dB; Interference voltage < 10 V		
Interrupts/diagnostics/status information			
Diagnostics function	Yes		
Alarms			
• Diagnostic alarm • Hardware interrupt	Yes; Parameterizable Yes; (limit value alarm), can be parameterized for channel 0		
Diagnoses			
• Diagnostic information readable • Wire-break • Short-circuit	Yes Yes; at 1 to 5 V Yes; at 1 to 5 V		
Diagnostics indication LED			
• Group error SF (red)	Yes		
Potential separation			
Potential separation analog inputs			
• between the channels • between the channels and backplane bus	No Yes		
Permissible potential difference			
Between the inputs and MANA (UCM)	10 Vpp AC		
Isolation			
Isolation tested with	707 V DC (type test)		
Dimensions			
Width	45 mm		
Height	130 mm		
Depth	35 mm		
Weights			
Weight, approx.	150 g		
Classifications			
		Version	Classification
	eClass	14	27-24-26-01
	eClass	12	27-24-26-01
	eClass	9.1	27-24-26-01
	eClass	9	27-24-26-01
	eClass	8	27-24-26-01
	eClass	7.1	27-24-26-01
	eClass	6	27-24-26-01
	ETIM	9	EC001596
	ETIM	8	EC001596
	ETIM	7	EC001596
	IDEA	4	3562
	UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval

[Manufacturer Declaration](#)


EG-Konf.




UL

[Metrological Approval](#)


RCM

General Product Approval

Marine / Shipping

[KC](#)


ABS




DNV


LRS

[NK / Nippon Kaiji Kyokai](#)

Marine / Shipping


RINA

[CCS \(China Classification Society\)](#)


Korea Register

last modified:

5/22/2024 