



SIMATIC ET 200AL, CM 4x IO-Link, 4x M12, Degree of protection IP67

General information	
Product type designation	CM 4x IO-Link
HW functional status	FS08
Firmware version	V1.2.x
Product function	
• I&M data	Yes; I&M0 to I&M3
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	STEP 7 V13 SP1 or higher
• STEP 7 configurable/integrated from version	From V5.5 SP4 Hotfix 3
• PROFIBUS from GSD version/GSD revision	GSD as of Revision 5
• PROFINET from GSD version/GSD revision	GSDML V2.3.1
Operating mode	
• IO-Link	Yes
• DI	Yes
• DQ	Yes; max. 100 mA
Supply voltage	
power supply according to NEC Class 2 required	No
Load voltage 1L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V
• Reverse polarity protection	Yes
Load voltage 2L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V
• Reverse polarity protection	Yes; against destruction; load increasing
Input current	
Current consumption (rated value)	40 mA; without load
from load voltage 1L+ (unswitched voltage)	4 A; Maximum value
from load voltage 2L+, max.	4 A; Maximum value
Encoder supply	
Number of outputs	4
24 V encoder supply	
• Short-circuit protection	Yes; per module, electronic
• Output current, max.	1.4 A; Total current of all ports
Power loss	
Power loss, typ.	2.6 W
IO-Link	
Number of ports	4

• of which simultaneously controllable	4		
IO-Link protocol 1.0	Yes		
IO-Link protocol 1.1	Yes		
Transmission rate	4.8 kBaud (COM1); 38.4 kBaud (COM2), 230 kBaud (COM3)		
Size of process data, input per port	32 byte		
Size of process data, input per module	132 byte		
Size of process data, output per port	32 byte		
Size of process data, output per module	128 byte		
Memory size for device parameter	2 kbyte; for each port		
Master backup	Possible with function block IO_LINK_MASTER		
Configuration without S7-PCT	Possible; autostart/manual function		
Cable length unshielded, max.	20 m		
Connection of IO-Link devices			
• Port type A	Yes; via 3-core cable		
• Port type B	Yes; Additional device supply: 1.6 A total current of all ports		
Interrupts/diagnostics/status information			
Alarms			
• Diagnostic alarm	Yes; Parameterizable		
Diagnoses			
• Monitoring the supply voltage	Yes		
• Wire-break	Yes		
• Short-circuit	Yes		
Diagnostics indication LED			
• Channel status display	Yes; green LED		
• for module diagnostics	Yes; green/red LED		
• For load voltage monitoring	Yes; green LED		
Potential separation			
between the load voltages	Yes		
Potential separation channels			
• between the channels	No		
• between the channels and backplane bus	Yes		
• between the channels and the power supply of the electronics	No		
Isolation			
Isolation tested with	707 V DC (type test)		
Degree and class of protection			
IP degree of protection	IP65/67		
Standards, approvals, certificates			
Suitable for safety-related tripping of standard modules	Yes; from FS01		
Highest safety class achievable for safety-related tripping of standard modules			
• Performance level according to ISO 13849-1	PL d		
• Category according to ISO 13849-1	Cat. 3		
• SILCL according to IEC 62061	SILCL 2		
Ambient conditions			
Ambient temperature during operation			
• min.	-30 °C		
• max.	55 °C		
connection method			
Design of electrical connection for the inputs and outputs	M12, 5-pole		
Design of electrical connection for supply voltage	M8, 4-pole		
ET-Connection			
• ET-Connection	M8, 4-pin, shielded		
Dimensions			
Width	30 mm		
Height	159 mm		
Depth	40 mm		
Weights			
Weight, approx.	145 g		
Classifications			
		Version	Classification

eClass	14	27-24-26-08
eClass	12	27-24-26-08
eClass	9.1	27-24-26-08
eClass	9	27-24-26-08
eClass	8	27-24-26-08
eClass	7.1	27-24-26-08
eClass	6	27-24-26-08
ETIM	9	EC001604
ETIM	8	EC001604
ETIM	7	EC001604
IDEA	4	3564
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval	EMV
--------------------------	-----



EG-Konf.



[KC](#)



UL



RCM

[KC](#)

last modified:

12/8/2024 