



label holder for self-inscription, flat, frame rounded off at the bottom for labeling plate 16.05 mm x 26.3 mm, for gluing, for the operator controls of the Extension Units for PRO devices (template for labeling for download is available), not suitable for labeling of EMERGENCY STOP button, scope of supply: 12 label holders, 12 transparent covers

General information	
Product type designation	Label holder
Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	50 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	3 500 m
Relative humidity	
• Operation, max.	90 %
• Condensation permissible	No
Mechanics/material	
Material	
• Plastic	Yes
Dimensions	
Width	29.9 mm
Height	50 mm
Depth	3.6 mm
Mounting diameter	22.3 mm
Weights	
Weight (without packaging)	33 g
Scope of supply	
Delivery quantity in pieces	
• Parts per unit	12
Components included	12 label holders, 12 transparent covers, installation instructions
Other	
printable with laser printer	Yes; Word template available for labeling in SIOS, writable surface area: 28 mm x 16 mm (width x height)
Target devices	Suitable for Extension Units of the 16:9 HMI/IPC PRO devices (refer to manual)
Usable in the following products	
• Product 1	6AV7674-1LA31-0AA0
• Product 2	6AV7674-1LA41-0AA0
• Product 3	6AV7674-1LA51-0AA0
• Product 4	6AV7674-1LA61-0AA0
• Product 5	6AV7674-1LA32-0AA0

- Product 6
- Product 7
- Product 8

[6AV7674-1LA42-0AA0](#)
[6AV7674-1LA52-0AA0](#)
[6AV7674-1LA62-0AA0](#)

Classifications

	Version	Classification
eClass	14	27-33-02-92
eClass	12	27-33-02-92
eClass	9.1	27-33-02-92
eClass	9	27-33-02-92
eClass	8	27-24-92-03
eClass	7.1	27-24-92-03
eClass	6	27-24-92-03
ETIM	9	EC002584
ETIM	8	EC002584
ETIM	7	EC002584
IDEA	4	3552
UNSPSC	15	32-15-17-03

last modified:

5/22/2024 