## **SIEMENS**

## **Data sheet**

## 6GK5108-0GA00-2AC2

SCALANCE XCM108 (8x100/1000 Mbps RJ45) unmanaged IE switch LED diagnostics, error-signaling contact with set pushbutton, redundant power supply manual available as a download

product type designation	
product brand name	SCALANCE
product type designation	XCM108
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s, 1000 Mbit/s
interfaces / for communication / integrated	
number of electrical connections	
<ul> <li>for network components or terminal equipment</li> </ul>	8; RJ45
number of 10/100/1000 Mbit/s RJ45 ports	
with securing collar	8
interfaces / other	
number of electrical connections	
for signaling contact	1
<ul><li>for power supply</li></ul>	1
type of electrical connection	
for signaling contact	2-pole terminal block
• for power supply	4-pole terminal block
operating voltage / of the signaling contacts	
at DC / rated value	24 V
operational current / of the signaling contacts	
at DC / maximum	0.1 A
supply voltage, current consumption, power loss	
product component / connection for redundant voltage supply	Yes
type of voltage / 1 / of the supply voltage	DC
<ul> <li>supply voltage / 1 / rated value</li> </ul>	24 V
power loss [W] / 1 / rated value	3.2 W
consumed current / 1 / at rated supply voltage / maximum	0.22 A
<ul> <li>supply voltage / 1 / rated value</li> </ul>	9.6 31.2 V
consumed current / 1 / maximum	0.45 A
<ul> <li>type of electrical connection / 1 / for power supply</li> </ul>	4-pole terminal block
<ul> <li>product component / 1 / fusing at power supply input</li> </ul>	Yes
fuse protection type / 1 / at input for supply voltage	2.5 A / 125 V
ambient conditions	
ambient temperature	
during operation	-40 +70 °C
during storage	-40 +85 °C
during transport	-40 +85 °C
relative humidity	
at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	
design	compact
width	60 mm
height	147 mm
depth	125 mm
net weight	0.504 kg
fastening method	
35 mm DIN-rail mounting	Yes
wall mounting	Yes
- · · · · <b>y</b>	

• S7-300 rail mounting	Yes
• S7-1500 rail mounting	Yes
product features, product functions, product components / gene	eral
number of automatically learnable MAC addresses	2048
product functions / management, configuration, engineering	
product function	
multiport mirroring	No
• CoS	Yes
<ul><li>switch-managed</li></ul>	No
PROFINET conformity class	A
product functions / redundancy	
product function	
<ul> <li>Parallel Redundancy Protocol (PRP)/operation in the PRP-network</li> </ul>	Yes
Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)	No
standards, specifications, approvals	
certificate of suitability	
• CE marking	Yes
UKCA marking     FO Poplaration of Conformity FN 64040 JEC 64040 4	Yes
<ul> <li>EC Declaration of Conformity EN 61010, IEC 61010-1, UL 61010A-1</li> </ul>	Yes
• KC approval	Yes
Regulatory Compliance Mark (RCM)	Yes
standard	EN 04000 0 4
• for EMC interference emission	EN 61000-6-4
• for immunity to EMC	EN 61000-6-2 UL 62368-1
for safety / from CSA and UL     standards, specifications, approvals / other	UL 02308-1
certificate of suitability  • RoHS conformity	Yes
resistance to air pollution / conformity according to ANSI/ISA-	Yes; G3
71.04	165, 65
product functions / general	
MTBF	73 a
reference code	
<ul> <li>according to IEC 81346-2</li> </ul>	KF
• according to IEC 81346-2:2019	KFE
Warranty period	5 a
product function / is supported / identification link	Yes; acc. to IEC 61406-1:2022
further information / internet links	
internet link	
<ul> <li>to website: Selection guide for cables and connectors</li> </ul>	https://support.industry.siemens.com/cs/ww/en/view/109766358
to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
to website: Industrial communication	https://www.siemens.com/simatic-net
to web page: SiePortal	https://sieportal.siemens.com/
to website: Image database	https://www.automation.siemens.com/bilddb
to website: CAx-Download-Manager     to website: Industry Online Cymnot	https://www.siemens.com/cax
to website: Industry Online Support	https://support.industry.siemens.com
security information	Circumstant and the second state of the second
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are

no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under https://www.siemens.com/cert. (V4.7)

## Approvals / Certificates

**General Product Approval** 





Miscellaneous

last modified: 2/26/2025 🖸