



SIMATIC ET 200SP, TM SIWAREX WP321 ST, single-channel weighing module for platform or hopper scales with analog load cells / strain gauges (full bridges), 1xRS485, 1xLC load cell interface (1-4mV/V), suitable for BU type A0, packing quantity: 1 unit, Detailed load cell diagnostics with digital junction box SIWAREX DB (7MH5001-0AD20 or 7MH5001-0AD01)

General information	
Product type designation	TM SIWAREX WP321 ST
HW functional status	FS04
Firmware version	V1.4.3
• FW update possible	Yes
usable BaseUnits	BU type A0
Color code for module-specific color identification plate	CC00
Product function	
• I&M data	Yes; I&M0 to I&M3
• Isochronous mode	No
• Adjustment of measuring range	No
Engineering with	
• STEP 7 TIA Portal configurable/integrated from version	STEP 7 V14 or higher
• STEP 7 configurable/integrated from version	From STEP 7 V5.4 and higher
• PROFIBUS from GSD version/GSD revision	GSD Revision 5
• PROFINET from GSD version/GSD revision	GSDML V2.34
Supply voltage	
Rated value (DC)	24 V
Load voltage L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	19.2 V
• permissible range, upper limit (DC)	28.8 V
• Short-circuit protection	Yes
• Reverse polarity protection	Yes
Input current	
Current consumption, max.	100 mA
Encoder supply	
Output voltage (DC)	4.85 V
Short-circuit protection	Yes
Power	
Power consumption from the backplane bus	70 mW
Power loss	
Power loss, typ.	2 W
Address area	
Address space per module	
• Inputs	16 byte
• Outputs	16 byte
Hardware configuration	
Automatic encoding	Yes
• Mechanical coding element	Yes

• Type of mechanical coding element	type B
<b>Encoder</b>	
Connection of signal encoders	
• For strain gauges (full bridges) with 4-conductor connection	Yes
• For strain gauges (full bridges) with 6-conductor connection	Yes
• Resistance of full bridge, min.	40 Ω; when using SIWAREX IS: 50 ohm for 7MH4710-5BA; 105 ohm when using 7MH4710-5CA
• Resistance of full bridge, max.	4 100 Ω
<b>Errors/accuracies</b>	
Linearity error (relative to input range), (+/-)	0.01 %
Error limit according to DIN 1319-1	0.05 %; of full-scale value
Temperature coefficient, zero point	≤ ±0.1 μV/K
Temperature coefficient, span	≤ ±5 ppm/K
Temperature coefficient, span, 4-wire connection (in relation to end value)	≤ ±5 ppm/K
Temperature coefficient, span, 6-wire connection (in relation to end value)	≤ ±10 ppm/K
<b>1. Interface</b>	
Interface types	
• RS 485	Yes; 390 Ω, 220 Ω, 390 Ω connectable termination
<b>Interface types</b>	
RS 485	
• Transmission rate, max.	115.2 kbit/s
• Cable length, max.	1 000 m; ≤ 115 kbps, shielded cable
<b>Interrupts/diagnostics/status information</b>	
Diagnostics function	Yes; Diagnostic alarm
Substitute values connectable	No
<b>Alarms</b>	
• Diagnostic alarm	Yes; Parameterizable
• Hardware interrupt	Yes; Parameterizable
<b>Diagnoses</b>	
• Monitoring the supply voltage	Yes
• Wire-break	Yes
• Short-circuit	Yes
• Group error	Yes
<b>Diagnostics indication LED</b>	
• ERROR LED	Yes; green/red DIAG LED
• Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
<b>Integrated Functions</b>	
Counter	No
<b>Load cell</b>	
• Non-automatic weighing instrument	NAWI
• permissible input signal per verification interval, min.	0.5 μV/d (d=e)
• Sampling rate	600 Hz
• Resolution of input signal	±500 000 parts pro mV/V
• Common mode voltage, min.	0.25 V
• Common mode voltage, max.	4.75 V
• input resistance of signal line, typ.	4 MΩ
• input resistance of sense line, typ.	2 MΩ
• Cable length, max.	500 m; when using the SIWAREX 7MH4702-8AG cable
<b>Measuring functions</b>	
Measuring range	
— -1 mV/V to +1 mV/V	Yes; corresponds to a resolution of ±500 000 parts
— -2 mV/V to +2 mV/V	Yes; corresponds to a resolution of ±1 000 000 parts
— -4 mV/V to +4 mV/V	Yes; corresponds to a resolution of ±2 000 000 parts
<b>Isolation</b>	
Isolation tested with	707 V DC (type test)
<b>Standards, approvals, certificates</b>	
Suitable for safety functions	No
<b>Ambient conditions</b>	

<b>Ambient temperature during operation</b>	
• horizontal installation, min.	-25 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	-25 °C
• vertical installation, max.	50 °C

<b>Altitude during operation relating to sea level</b>	
• Installation altitude above sea level, max.	5 000 m; more than 2 000 m above sea level, the ambient temperature is reduced by -1 °C per 100 m
• Ambient air temperature-barometric pressure-altitude	1 080 ... 795 hPa (-1 000 ... 5 000 m above sea level)

<b>Decentralized operation</b>	
to SIMATIC S7-300	Yes
to SIMATIC S7-400	Yes
to SIMATIC S7-1200	Yes
to SIMATIC S7-1500	Yes
to standard PROFIBUS master	Yes
to standard PROFINET controller	Yes

<b>Dimensions</b>	
Width	15 mm
Height	73 mm
Depth	58 mm

<b>Weights</b>	
Weight, approx.	30 g

<b>Classifications</b>			
		<b>Version</b>	<b>Classification</b>
	eClass	14	27-32-03-01
	eClass	12	27-32-03-01
	eClass	9.1	27-32-03-01
	eClass	9	27-32-03-01
	eClass	8	27-32-03-01
	eClass	7.1	27-32-03-01
	eClass	6	27-32-03-01
	ETIM	9	EC003997
	ETIM	8	EC003997

**Approvals / Certificates**

**General Product Approval**

[Confirmation](#)



[KC](#)

**For use in hazardous locations**

[FM](#)



[Miscellaneous](#)



last modified:

2/28/2025