



SIMATIC ET 200SP, BusAdapter BA-SEND BA1XFC, 1x FastConnect connection for ET connection

General information			
Product type designation	BA-Send 1xFC		
HW functional status	From FS05		
Interfaces			
Supports protocol for PROFINET IO			
Cable length	15 m; from IM firmware V3.3: between BA-send and the first ET-CONNECTION bus node and between all other bus nodes		
— Cu conductors			
ET-Connection			
• Number of interfaces ET connection	1		
• FC (FastConnect)	Yes		
Ambient conditions			
Ambient temperature during operation			
• horizontal installation, min.	-30 °C		
• horizontal installation, max.	60 °C		
• vertical installation, min.	-30 °C		
• vertical installation, max.	50 °C		
Altitude during operation relating to sea level			
• Installation altitude above sea level, max.	5 000 m; restrictions for installation altitudes > 2 000 m, see ET 200SP system manual		
Dimensions			
Width	20 mm		
Height	69.5 mm		
Depth	59 mm		
Weights			
Weight, approx.	44 g		
Classifications			
		Version	Classification
	eClass	14	27-24-26-92
	eClass	12	27-24-26-92
	eClass	9.1	27-24-26-92
	eClass	9	27-24-26-92
	eClass	8	27-24-26-92
	eClass	7.1	27-24-26-92
	eClass	6	27-24-26-92
	ETIM	9	EC002584
	ETIM	8	EC002584
ETIM	7	EC002584	

IDEA	4	3552
UNSPSC	15	32-15-17-03

Approvals / Certificates

General Product Approval



[Manufacturer Declaration](#)

[KC](#)


For use in hazardous locations


[FM](#)
[CCC-Ex](#)


[Miscellaneous](#)

Marine / Shipping





[NK / Nippon Kaiji Kyokai](#)


Marine / Shipping


[CCS \(China Classification Society\)](#)


last modified: 5/22/2024 