

SIPLUS HMI TP900 Comfort based on 6AV2124-0JC01-0AX0 with conformal coating, 0...+50 °C,



Figure similar

| General information                                                   |                                    |
|-----------------------------------------------------------------------|------------------------------------|
| Product type designation                                              | TP900 Comfort                      |
| based on                                                              | <a href="#">6AV2124-0JC01-0AX0</a> |
| Display                                                               |                                    |
| Design of display                                                     | TFT                                |
| Screen diagonal                                                       | 9 in                               |
| Display width                                                         | 195 mm                             |
| Display height                                                        | 117 mm                             |
| Number of colors                                                      | 16 777 216                         |
| Resolution (pixels)                                                   |                                    |
| • Horizontal image resolution                                         | 800 pixel                          |
| • Vertical image resolution                                           | 480 pixel                          |
| Backlighting                                                          |                                    |
| • MTBF backlighting (at 25 °C)                                        | 80 000 h                           |
| • Backlight dimmable                                                  | Yes; 0-100 %                       |
| Control elements                                                      |                                    |
| Keyboard fonts                                                        |                                    |
| • Function keys                                                       |                                    |
| — Number of function keys                                             | 0                                  |
| — Number of function keys with LEDs                                   | 0                                  |
| • Keys with LED                                                       | No                                 |
| • System keys                                                         | No                                 |
| • Numeric keyboard                                                    | Yes; Onscreen keyboard             |
| • alphanumeric keyboard                                               | Yes; Onscreen keyboard             |
| Touch operation                                                       |                                    |
| • Design as touch screen                                              | Yes; Analog-resistive              |
| Expansions for operator control of the process                        |                                    |
| • DP direct LEDs (LEDs as S7 output I/O)                              |                                    |
| — F1...Fx                                                             | 0                                  |
| • Direct keys (keys as S7 input I/O)                                  |                                    |
| — F1...Fx                                                             | 0                                  |
| • Direct keys (touch buttons as S7 input I/O)                         | 40                                 |
| Installation type/mounting                                            |                                    |
| Mounting position                                                     | vertical                           |
| Wall mounting/direct mounting                                         | No                                 |
| Mounting in portrait format possible                                  | Yes                                |
| Mounting in landscape format possible                                 | Yes                                |
| maximum permissible angle of inclination without external ventilation | 35°                                |

|                                            |                                         |
|--------------------------------------------|-----------------------------------------|
| <b>Supply voltage</b>                      |                                         |
| Type of supply voltage                     | DC                                      |
| Rated value (DC)                           | 24 V                                    |
| permissible range, lower limit (DC)        | 19.2 V                                  |
| permissible range, upper limit (DC)        | 28.8 V                                  |
| <b>Input current</b>                       |                                         |
| Current consumption (rated value)          | 0.75 A                                  |
| Starting current inrush I <sub>t</sub>     | 0.5 A <sup>2</sup> ·s                   |
| <b>Power</b>                               |                                         |
| Active power input, typ.                   | 18 W                                    |
| <b>Processor</b>                           |                                         |
| Processor type                             | X86                                     |
| <b>Memory</b>                              |                                         |
| Flash                                      | Yes                                     |
| RAM                                        | Yes                                     |
| Memory available for user data             | 12 Mbyte                                |
| <b>Type of output</b>                      |                                         |
| Info LED                                   | No                                      |
| Power LED                                  | No                                      |
| Error LED                                  | No                                      |
| Acoustics                                  |                                         |
| • Buzzer                                   | No                                      |
| • Speaker                                  | Yes                                     |
| <b>Time of day</b>                         |                                         |
| Clock                                      |                                         |
| • Hardware clock (real-time)               | Yes                                     |
| • Software clock                           | No                                      |
| • retentive                                | Yes; Back-up duration typically 6 weeks |
| • synchronizable                           | Yes                                     |
| <b>Interfaces</b>                          |                                         |
| Number of industrial Ethernet interfaces   | 2                                       |
| Number of RS 485 interfaces                | 1; RS 422 / 485 combined                |
| Number of RS 422 interfaces                | 1                                       |
| Number of RS 232 interfaces                | 0                                       |
| Number of USB interfaces                   | 2; USB 2.0                              |
| • USB Mini B                               | 1; 5-pole                               |
| Number of 20 mA interfaces (TTY)           | 0                                       |
| Number of parallel interfaces              | 0                                       |
| Number of other interfaces                 | 0                                       |
| Number of SD card slots                    | 2                                       |
| With software interfaces                   | No                                      |
| <b>Industrial Ethernet</b>                 |                                         |
| • Industrial Ethernet status LED           | 2                                       |
| • Number of ports of the integrated switch | 2                                       |
| <b>Protocols</b>                           |                                         |
| PROFINET                                   | Yes                                     |
| Supports protocol for PROFINET IO          | Yes                                     |
| IRT                                        | Yes; As of WinCC V12                    |
| PROFIBUS                                   | Yes                                     |
| EtherNet/IP                                | Yes                                     |
| MPI                                        | Yes                                     |
| <b>Protocols (Ethernet)</b>                |                                         |
| • TCP/IP                                   | Yes                                     |
| • DHCP                                     | Yes                                     |
| • SNMP                                     | Yes                                     |
| • DCP                                      | Yes                                     |
| • LLDP                                     | Yes                                     |
| <b>WEB characteristics</b>                 |                                         |
| • HTTP                                     | Yes                                     |
| • HTTPS                                    | No                                      |

|                                                                     |                                                                                                                                                                                                                 |
|---------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| • HTML                                                              | Yes                                                                                                                                                                                                             |
| • XML                                                               | No                                                                                                                                                                                                              |
| • CSS                                                               | Yes                                                                                                                                                                                                             |
| • Active X                                                          | No                                                                                                                                                                                                              |
| • JavaScript                                                        | Yes                                                                                                                                                                                                             |
| • Java VM                                                           | No                                                                                                                                                                                                              |
| Redundancy mode                                                     |                                                                                                                                                                                                                 |
| Media redundancy                                                    |                                                                                                                                                                                                                 |
| — MRP                                                               | Yes; As of WinCC V12                                                                                                                                                                                            |
| Further protocols                                                   |                                                                                                                                                                                                                 |
| • CAN                                                               | No                                                                                                                                                                                                              |
| • MODBUS                                                            | Yes                                                                                                                                                                                                             |
| EMC                                                                 |                                                                                                                                                                                                                 |
| Emission of radio interference acc. to EN 55 011                    |                                                                                                                                                                                                                 |
| • Limit class A, for use in industrial areas                        | Yes                                                                                                                                                                                                             |
| • Limit class B, for use in residential areas                       | No                                                                                                                                                                                                              |
| Degree and class of protection                                      |                                                                                                                                                                                                                 |
| IP (at the front)                                                   | IP65                                                                                                                                                                                                            |
| IP (rear)                                                           | IP20                                                                                                                                                                                                            |
| NEMA (front)                                                        |                                                                                                                                                                                                                 |
| • Enclosure Type 4 at the front                                     | Yes                                                                                                                                                                                                             |
| • Enclosure Type 4x at the front                                    | Yes                                                                                                                                                                                                             |
| Standards, approvals, certificates                                  |                                                                                                                                                                                                                 |
| Ecological footprint                                                |                                                                                                                                                                                                                 |
| • environmental product declaration                                 | Yes                                                                                                                                                                                                             |
| Global warming potential                                            |                                                                                                                                                                                                                 |
| — global warming potential, (total) [CO2 eq]                        | 254 kg                                                                                                                                                                                                          |
| — global warming potential, (during production) [CO2 eq]            | 61.5 kg                                                                                                                                                                                                         |
| — global warming potential, (during operation) [CO2 eq]             | 194 kg                                                                                                                                                                                                          |
| — global warming potential, (after end of life cycle) [CO2 eq]      | -1.87 kg                                                                                                                                                                                                        |
| Ambient conditions                                                  |                                                                                                                                                                                                                 |
| Suited for indoor use                                               | Yes                                                                                                                                                                                                             |
| Suited for outdoor use                                              | No                                                                                                                                                                                                              |
| Ambient temperature during operation                                |                                                                                                                                                                                                                 |
| Operation (vertical installation)                                   |                                                                                                                                                                                                                 |
| — For vertical installation, min.                                   | 0 °C; = Tmin                                                                                                                                                                                                    |
| — For vertical installation, max.                                   | 50 °C; = Tmax                                                                                                                                                                                                   |
| Operation (max. tilt angle)                                         |                                                                                                                                                                                                                 |
| — At maximum tilt angle, min.                                       | 0 °C; = Tmin                                                                                                                                                                                                    |
| — At maximum tilt angle, max.                                       | 40 °C; = Tmax                                                                                                                                                                                                   |
| Operation (vertical installation, portrait format)                  |                                                                                                                                                                                                                 |
| — For vertical installation, min.                                   | 0 °C; = Tmin                                                                                                                                                                                                    |
| — For vertical installation, max.                                   | 40 °C; = Tmax                                                                                                                                                                                                   |
| Operation (max. tilt angle, portrait format)                        |                                                                                                                                                                                                                 |
| — At maximum tilt angle, min.                                       | 0 °C; = Tmin                                                                                                                                                                                                    |
| — At maximum tilt angle, max.                                       | 35 °C; = Tmax                                                                                                                                                                                                   |
| Ambient temperature during storage/transportation                   |                                                                                                                                                                                                                 |
| • min.                                                              | -20 °C                                                                                                                                                                                                          |
| • max.                                                              | 60 °C                                                                                                                                                                                                           |
| Altitude during operation relating to sea level                     |                                                                                                                                                                                                                 |
| • Installation altitude above sea level, max.                       | 5 000 m                                                                                                                                                                                                         |
| • Ambient air temperature-barometric pressure-altitude              | Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m) |
| Relative humidity                                                   |                                                                                                                                                                                                                 |
| • With condensation, tested in accordance with IEC 60068-2-38, max. | 100 %; RH incl. condensation/frost (no commissioning under condensation conditions)                                                                                                                             |
| Resistance                                                          |                                                                                                                                                                                                                 |
| Coolants and lubricants                                             |                                                                                                                                                                                                                 |

|                                                                                                                         |                                                                                                                                                                                     |
|-------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| — Resistant to commercially available coolants and lubricants                                                           | Yes; Incl. diesel and oil droplets in the air                                                                                                                                       |
| <b>Use in stationary industrial systems</b>                                                                             |                                                                                                                                                                                     |
| — to biologically active substances according to EN 60721-3-3                                                           | Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request                                                                                  |
| — to chemically active substances according to EN 60721-3-3                                                             | Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *                                                                                            |
| — to mechanically active substances according to EN 60721-3-3                                                           | Yes; Class 3S4 incl. sand, dust, *                                                                                                                                                  |
| <b>Use on ships/at sea</b>                                                                                              |                                                                                                                                                                                     |
| — to biologically active substances according to EN 60721-3-6                                                           | Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request                                                                                                       |
| — to chemically active substances according to EN 60721-3-6                                                             | Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *                                                                                            |
| — to mechanically active substances according to EN 60721-3-6                                                           | Yes; Class 6S3 incl. sand, dust; *                                                                                                                                                  |
| <b>Usage in industrial process technology</b>                                                                           |                                                                                                                                                                                     |
| — Against chemically active substances acc. to EN 60654-4                                                               | Yes; Class 3 (excluding trichlorethylene)                                                                                                                                           |
| — Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04                            | Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil) |
| <b>Remark</b>                                                                                                           |                                                                                                                                                                                     |
| — Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04             | * The supplied plug covers must remain in place over the unused interfaces during operation!                                                                                        |
| <b>Conformal coating</b>                                                                                                |                                                                                                                                                                                     |
| • Coatings for printed circuit board assemblies acc. to EN 61086                                                        | Yes; Class 2 for high reliability                                                                                                                                                   |
| • Protection against fouling acc. to EN 60664-3                                                                         | Yes; Type 1 protection                                                                                                                                                              |
| • Military testing according to MIL-I-46058C, Amendment 7                                                               | Yes; Discoloration of coating possible during service life                                                                                                                          |
| • Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A | Yes; Conformal coating, Class A                                                                                                                                                     |
| <b>Operating systems</b>                                                                                                |                                                                                                                                                                                     |
| proprietary                                                                                                             | No                                                                                                                                                                                  |
| <b>pre-installed operating system</b>                                                                                   |                                                                                                                                                                                     |
| • Windows CE                                                                                                            | Yes                                                                                                                                                                                 |
| <b>configuration / header</b>                                                                                           |                                                                                                                                                                                     |
| Message indicator                                                                                                       | Yes                                                                                                                                                                                 |
| Alarm system (incl. buffer and acknowledgment)                                                                          | Yes                                                                                                                                                                                 |
| Process value display (output)                                                                                          | Yes                                                                                                                                                                                 |
| Process value default (input) possible                                                                                  | Yes                                                                                                                                                                                 |
| Recipe management                                                                                                       | Yes                                                                                                                                                                                 |
| <b>Configuration software</b>                                                                                           |                                                                                                                                                                                     |
| • STEP 7 Basic (TIA Portal)                                                                                             | No                                                                                                                                                                                  |
| • STEP 7 Professional (TIA Portal)                                                                                      | No                                                                                                                                                                                  |
| • WinCC flexible Compact                                                                                                | No                                                                                                                                                                                  |
| • WinCC flexible Standard                                                                                               | No                                                                                                                                                                                  |
| • WinCC flexible Advanced                                                                                               | No                                                                                                                                                                                  |
| • WinCC Basic (TIA Portal)                                                                                              | No                                                                                                                                                                                  |
| • WinCC Comfort (TIA Portal)                                                                                            | Yes; from V11                                                                                                                                                                       |
| • WinCC Advanced (TIA Portal)                                                                                           | Yes; from V11                                                                                                                                                                       |
| • WinCC Professional (TIA Portal)                                                                                       | Yes; from V11                                                                                                                                                                       |
| <b>Languages</b>                                                                                                        |                                                                                                                                                                                     |
| <b>Online languages</b>                                                                                                 |                                                                                                                                                                                     |
| • Number of online/runtime languages                                                                                    | 32                                                                                                                                                                                  |
| <b>Project languages</b>                                                                                                |                                                                                                                                                                                     |
| • Languages per project                                                                                                 | 32                                                                                                                                                                                  |
| <b>Functionality under WinCC (TIA Portal)</b>                                                                           |                                                                                                                                                                                     |
| Libraries                                                                                                               | Yes                                                                                                                                                                                 |
| <b>Applications/options</b>                                                                                             |                                                                                                                                                                                     |
| • Web browser                                                                                                           | Yes                                                                                                                                                                                 |
| • Pocket Word                                                                                                           | Yes                                                                                                                                                                                 |
| • Pocket Excel                                                                                                          | Yes                                                                                                                                                                                 |

|                                                              |         |
|--------------------------------------------------------------|---------|
| • PDF Viewer                                                 | Yes     |
| • Media Player                                               | Yes     |
| • SIMATIC WinCC Sm@rtServer                                  | Yes     |
| • SIMATIC WinCC Audit                                        | Yes     |
| Number of Visual Basic Scripts                               | Yes     |
| Task planner                                                 |         |
| • time-controlled                                            | Yes     |
| • task-controlled                                            | Yes     |
| Help system                                                  |         |
| • Number of characters per info text                         | 70      |
| Message system                                               |         |
| • Number of alarm classes                                    | 32      |
| • Bit messages                                               |         |
| — Number of bit messages                                     | 4 000   |
| • Analog messages                                            |         |
| — Number of analog messages                                  | 200     |
| • S7 alarm number procedure                                  | Yes     |
| • System messages HMI                                        | Yes     |
| • System event, more (SIMATIC S7, SINUMERIK, SIMOTION, ... ) | Yes     |
| • Number of characters per message                           | 80      |
| • Number of process values per message                       | 8       |
| • Acknowledgment groups                                      | Yes     |
| • Message indicator                                          | Yes     |
| • Message buffer                                             |         |
| — Number of entries                                          | 1 024   |
| — Circulating buffer                                         | Yes     |
| — retentive                                                  | Yes     |
| — maintenance-free                                           | Yes     |
| Recipe management                                            |         |
| • Number of recipes                                          | 300     |
| • Data records per recipe                                    | 500     |
| • Entries per data record                                    | 1 000   |
| • Size of internal recipe memory                             | 2 Mbyte |
| • Recipe memory expandable                                   | Yes     |
| Variables                                                    |         |
| • Number of variables per device                             | 2 048   |
| • Number of variables per screen                             | 400     |
| • Limit values                                               | Yes     |
| • Multiplexing                                               | Yes     |
| • Structures                                                 | Yes     |
| • Arrays                                                     | Yes     |
| Images                                                       |         |
| • Number of configurable images                              | 500     |
| • Permanent window/default                                   | Yes     |
| • Global image                                               | Yes     |
| • Image selection by PLC                                     | Yes     |
| • Image number in the PLC                                    | Yes     |
| Image objects                                                |         |
| • Number of objects per image                                | 400     |
| • Text fields                                                | Yes     |
| • I/O fields                                                 | Yes     |
| • Graphic I/O fields (graphics list)                         | Yes     |
| • Symbolic I/O fields (text list)                            | Yes     |
| • Date/time fields                                           | Yes     |
| • Switches                                                   | Yes     |
| • Buttons                                                    | Yes     |
| • Graphic display                                            | Yes     |
| • Icons                                                      | Yes     |
| • Geometric objects                                          | Yes     |
| Complex image objects                                        |         |

|                                        |     |
|----------------------------------------|-----|
| • Number of complex objects per screen | 20  |
| • Alarm view                           | Yes |
| • Trend view                           | Yes |
| • User view                            | Yes |
| • Status/control                       | Yes |
| • Sm@rtClient view                     | Yes |
| • Recipe view                          | Yes |
| • f(x) trend view                      | Yes |
| • System diagnostics view              | Yes |
| • Media Player                         | Yes |
| • Bar graphs                           | Yes |
| • Sliders                              | Yes |
| • Pointer instruments                  | Yes |
| • Analog/digital clock                 | Yes |

#### Lists

|                                        |     |
|----------------------------------------|-----|
| • Number of text lists per project     | 500 |
| • Number of entries per text list      | 500 |
| • Number of graphics lists per project | 500 |
| • Number of entries per graphics list  | 500 |

#### Archiving

|                                 |        |
|---------------------------------|--------|
| • Number of archives per device | 50     |
| • Number of entries per archive | 20 000 |
| • Message archive               | Yes    |
| • Process value archive         | Yes    |
| • Archiving methods             |        |
| — Sequential archive            | Yes    |
| — Short-term archive            | Yes    |
| • Memory location               |        |
| — Memory card                   | Yes    |
| — USB memory                    | Yes    |
| — Ethernet                      | Yes    |
| • Data storage format           |        |
| — CSV                           | Yes    |
| — TXT                           | Yes    |
| — RDB                           | Yes    |

#### Security

|                          |     |
|--------------------------|-----|
| • Number of user groups  | 50  |
| • Number of user rights  | 32  |
| • Number of users        | 50  |
| • Password export/import | Yes |
| • SIMATIC Logon          | Yes |

#### Logging through printer

|                            |                |
|----------------------------|----------------|
| • Alarms                   | Yes            |
| • Report (shift log)       | Yes            |
| • Hardcopy                 | Yes            |
| • Electronic print to file | Yes; PDF, HTML |

#### Character sets

|                  |     |
|------------------|-----|
| • Keyboard fonts |     |
| — US English     | Yes |

#### Transfer (upload/download)

|                                 |     |
|---------------------------------|-----|
| • MPI/PROFIBUS DP               | Yes |
| • USB                           | Yes |
| • Ethernet                      | Yes |
| • using external storage medium | No  |

#### Process coupling

|              |     |
|--------------|-----|
| • S7-1200    | Yes |
| • S7-1500    | Yes |
| • S7-200     | Yes |
| • S7-300/400 | Yes |
| • LOGO!      | Yes |
| • WinAC      | Yes |

|                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                               |         |                |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|---------|----------------|
| <ul style="list-style-type: none"><li>• SINUMERIK</li><li>• SIMOTION</li><li>• Allen Bradley (EtherNet/IP)</li><li>• Allen Bradley (DF1)</li><li>• Mitsubishi (MC TCP/IP)</li><li>• Mitsubishi (FX)</li><li>• OMRON (FINS TCP)</li><li>• OMRON (LINK/Multilink)</li><li>• Modicon (Modbus TCP/IP)</li><li>• Modicon (Modbus)</li><li>• OPC UA Client</li><li>• OPC UA Server</li></ul> | Yes; with SINUMERIK option package<br>No; With WinCC, subsequent version<br>Yes<br>Yes<br>Yes<br>Yes<br>No<br>Yes<br>Yes<br>Yes<br>Yes<br>Yes |         |                |
| Service tools/configuration aids                                                                                                                                                                                                                                                                                                                                                       |                                                                                                                                               |         |                |
| <ul style="list-style-type: none"><li>• Backup/Restore manually</li><li>• Backup/Restore automatically</li><li>• Simulation</li><li>• Device switchover</li></ul>                                                                                                                                                                                                                      | Yes<br>Yes<br>Yes<br>Yes                                                                                                                      |         |                |
| Peripherals/Options                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                               |         |                |
| Printer                                                                                                                                                                                                                                                                                                                                                                                | Yes                                                                                                                                           |         |                |
| SIMATIC HMI MM memory card: Multi Media Card                                                                                                                                                                                                                                                                                                                                           | Yes                                                                                                                                           |         |                |
| SIMATIC HMI SD memory card: Secure Digital memory card                                                                                                                                                                                                                                                                                                                                 | Yes                                                                                                                                           |         |                |
| USB memory                                                                                                                                                                                                                                                                                                                                                                             | Yes                                                                                                                                           |         |                |
| Network camera                                                                                                                                                                                                                                                                                                                                                                         | Yes                                                                                                                                           |         |                |
| Mechanics/material                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                                                               |         |                |
| Enclosure material (front) <ul style="list-style-type: none"><li>• Plastic</li><li>• Aluminum</li><li>• Stainless steel</li></ul>                                                                                                                                                                                                                                                      | No<br>Yes<br>No                                                                                                                               |         |                |
| Dimensions                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                               |         |                |
| Width of the housing front                                                                                                                                                                                                                                                                                                                                                             | 274 mm                                                                                                                                        |         |                |
| Height of housing front                                                                                                                                                                                                                                                                                                                                                                | 190 mm                                                                                                                                        |         |                |
| Mounting cutout, width                                                                                                                                                                                                                                                                                                                                                                 | 251 mm                                                                                                                                        |         |                |
| Mounting cutout, height                                                                                                                                                                                                                                                                                                                                                                | 166 mm                                                                                                                                        |         |                |
| Overall depth                                                                                                                                                                                                                                                                                                                                                                          | 63 mm                                                                                                                                         |         |                |
| Weights                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                                                               |         |                |
| Weight (without packaging)                                                                                                                                                                                                                                                                                                                                                             | 1.9 kg                                                                                                                                        |         |                |
| Weight (with packaging)                                                                                                                                                                                                                                                                                                                                                                | 2.6 kg                                                                                                                                        |         |                |
| Classifications                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                               |         |                |
|                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                               | Version | Classification |
|                                                                                                                                                                                                                                                                                                                                                                                        | eClass                                                                                                                                        | 14      | 27-33-02-01    |
|                                                                                                                                                                                                                                                                                                                                                                                        | eClass                                                                                                                                        | 12      | 27-33-02-01    |
|                                                                                                                                                                                                                                                                                                                                                                                        | eClass                                                                                                                                        | 9.1     | 27-33-02-01    |
|                                                                                                                                                                                                                                                                                                                                                                                        | eClass                                                                                                                                        | 9       | 27-33-02-01    |
|                                                                                                                                                                                                                                                                                                                                                                                        | eClass                                                                                                                                        | 8       | 27-24-23-02    |
|                                                                                                                                                                                                                                                                                                                                                                                        | eClass                                                                                                                                        | 7.1     | 27-24-23-02    |
|                                                                                                                                                                                                                                                                                                                                                                                        | eClass                                                                                                                                        | 6       | 27-24-23-02    |
|                                                                                                                                                                                                                                                                                                                                                                                        | ETIM                                                                                                                                          | 9       | EC001412       |
|                                                                                                                                                                                                                                                                                                                                                                                        | ETIM                                                                                                                                          | 8       | EC001412       |
|                                                                                                                                                                                                                                                                                                                                                                                        | ETIM                                                                                                                                          | 7       | EC001412       |
|                                                                                                                                                                                                                                                                                                                                                                                        | IDEA                                                                                                                                          | 4       | 6607           |
|                                                                                                                                                                                                                                                                                                                                                                                        | UNSPSC                                                                                                                                        | 15      | 43-21-15-06    |
| Approvals / Certificates                                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                               |         |                |
| General Product Approval                                                                                                                                                                                                                                                                                                                                                               |                                                                                                                                               |         | EMV            |

[Miscellaneous](#)



[Manufacturer Declaration](#)



[KC](#)

| EMV                                                                                      | For use in hazardous locations                                                             |                                                                                           |                        | Marine / Shipping                                                                           | Environment                                                                                |
|------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------|------------------------|---------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|
| <br>RCM | <br>IECEX | <br>ATEX | <a href="#">CCC-Ex</a> | <br>RMRS | <br>EPD |

last modified: 10/9/2024 