

SIMATIC DP, Y cable for ET 200 distributed I/O For double connection of I/Os via single cable to ET 200 5-pole M12, 200mm



Figure similar

General information			
Product type designation	Y cable		
Degree and class of protection			
IP degree of protection	IP67		
Ambient conditions			
Ambient temperature during assembly, min.	-25 °C		
Ambient temperature during assembly, max.	85 °C		
Ambient temperature during storage/transportation			
• min.	-50 °C		
• max.	80 °C		
Cables			
Cable designation	Li9Y11Y 4x 0.34 mm <sup>2</sup>		
Cable length	0.19 m		
Color of core insulation of energy core	white / brown / blue / black		
Mechanics/material			
Outgoing feeder type	180° cable outlet		
Material of cable sheath	PUR		
Material of core insulation	PP		
Material property			
• Halogen-free	Yes		
• Silicone-free	Yes		
Classifications			
		<b>Version</b>	<b>Classification</b>
	eClass	14	27-24-22-20
	eClass	12	27-24-22-20
	eClass	9.1	27-24-22-20
	eClass	9	27-24-22-20
	eClass	8	27-24-92-05
	eClass	7.1	27-24-92-05
	eClass	6	27-24-92-05
	ETIM	9	EC000237
	ETIM	8	EC000237
	ETIM	7	EC000237
	IDEA	4	3553
	UNSPSC	15	32-15-17-03
Approvals / Certificates			

General Product Approval

[Manufacturer Declaration](#)



[KC](#)



EMV

Marine / Shipping



last modified:

10/18/2024 