



SIMATIC S7-1200, Relay output SM 1226, F-DQ 2x RLY 5A, PROFIsafe, 70 mm overall width, up to PL E (ISO 13849-1)/ SIL3 (IEC 61508)

General information	
Product type designation	SM 1226, F-DQ 2x relay/5 A
Supply voltage	
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
power supply according to NEC Class 2 required	No
Input current	
from backplane bus 5 V DC, max.	120 mA
Digital outputs	
• from load voltage L+, max.	300 mA
Power loss	
Power loss, typ.	10 W
Digital outputs	
Number of digital outputs	2
Short-circuit protection	No
Output voltage	
• Rated value (DC)	5 V DC to 30 V DC
• Rated value (AC)	5 V AC to 250 V AC
Output current	
• for signal "1" permissible range, max.	5 A maximum per circuit and 10 A maximum of all circuits per module
Relay outputs	
• Number of relay outputs	2; 2 circuits per output
Switching capacity of contacts	
— with inductive load, max.	0.1 Hz, accordance with IEC 60947-5-1, DC-13; 2 Hz, accordance with IEC 60947-5-1, AC-15
— with resistive load, max.	2 Hz
Cable length	
• shielded, max.	200 m
• unshielded, max.	200 m
Interrupts/diagnostics/status information	
Diagnostics indication LED	
• for status of the outputs	Yes
Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
CE mark	Yes
cULus	Yes
FM approval	Yes
Highest safety class achievable in safety mode	
• Performance level according to ISO 13849-1	Category 4, PL e

• SIL acc. to IEC 61508	SIL 3
Probability of failure (for service life of 20 years and repair time of 100 hours)	
— Low demand mode: PFDavg in accordance with SIL3	< 1.00E-05
— High demand/continuous mode: PFH in accordance with SIL3	< 4.00E-09

Ambient conditions

Free fall

• Fall height, max.	0.3 m; five times, in product package
---------------------	---------------------------------------

Ambient temperature during operation

• min.	0 °C
• max.	55 °C
• permissible temperature change	5°C to 55°C, 3°C / minute

Ambient temperature during storage/transportation

• min.	-40 °C
• max.	70 °C

Air pressure acc. to IEC 60068-2-13

• Storage/transport, min.	660 hPa
• Storage/transport, max.	1 080 hPa

Relative humidity

• Operation at 25 °C without condensation, max.	95 %
---	------

Mechanics/material

Enclosure material (front)	
• Plastic	Yes

Dimensions

Width	70 mm
Height	100 mm
Depth	75 mm

Weights

Weight, approx.	300 g
-----------------	-------

Classifications

	Version	Classification
eClass	14	27-24-22-04
eClass	12	27-24-22-04
eClass	9.1	27-24-22-04
eClass	9	27-24-22-04
eClass	8	27-24-22-04
eClass	7.1	27-24-22-04
eClass	6	27-24-22-04
ETIM	9	EC001419
ETIM	8	EC001419
ETIM	7	EC001419
IDEA	4	3566
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval	EMV	For use in hazardous locations
--------------------------	-----	--------------------------------



FM

Functional Safety



[Type Examination Certificate](#)

last modified:

3/12/2024 