SIEMENS

Data sheet 6ES7223-1PH32-0XB0



Figure similar

SIMATIC S7-1200, Digital I/O SM 1223, 8 DI/8 DO, 8 DI 24 V DC, Sink/Source, 8 DO, relay 2 A

General information	
Product type designation	SM 1223, DI 8x24 V DC, DQ 8x relay
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
from backplane bus 5 V DC, max.	145 mA
Digital inputs	
● from load voltage L+ (without load), max.	4 mA/input 11 mA/relay
Output voltage	
Power supply to the transmitters	
● present	Yes
Power loss	
Power loss, typ.	5.5 W
Digital inputs	
Number of digital inputs	8
● in groups of	2
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Number of simultaneously controllable inputs	
all mounting positions	
— up to 40 °C, max.	8
horizontal installation	
— up to 40 °C, max.	8
— up to 50 °C, max.	8
vertical installation	
— up to 40 °C, max.	8
Input voltage	
● Rated value (DC)	24 V
● for signal "0"	5 V DC at 1 mA
● for signal "1"	15 V DC at 2.5 mA
Input current	
● for signal "0", max. (permissible quiescent current)	1 mA
● for signal "1", min.	2.5 mA
● for signal "1", typ.	4 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; 0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in

Subject to change without notice
© Copyright Siemens

	groups of four
for interrupt inputs	
— Parameterizable	Yes
Cable length	
● shielded, max.	500 m
● unshielded, max.	300 m
Digital outputs	
Number of digital outputs	8
● in groups of	2
Short-circuit protection	No; to be provided externally
Switching capacity of the outputs	
● with resistive load, max.	2 A
● on lamp load, max.	30 W with DC, 200 W with AC
Output voltage	
● Rated value (DC)	5 V DC to 30 V DC
● Rated value (AC)	5 V AC to 250 V AC
Output current	
● for signal "1" rated value	2 A
● for signal "1" permissible range, max.	2 A
Output delay with resistive load	
● "0" to "1", max.	10 ms
● "1" to "0", max.	10 ms
Total current of the outputs (per group)	
horizontal installation	
— up to 50 °C, max.	10 A; Current per mass
Relay outputs	
● Number of relay outputs	8
● Rated supply voltage of relay coil L+ (DC)	24 V
● Number of operating cycles, max.	mechanically 10 million, at rated load voltage 100 000
Switching capacity of contacts	
— with inductive load, max.	2 A
— on lamp load, max.	30 W with DC, 200 W with AC
— with resistive load, max.	2 A
Cable length	
● shielded, max.	500 m
● unshielded, max.	150 m
Interrupts/diagnostics/status information	
Alarms	
● Diagnostic alarm	Yes
Diagnostics indication LED	
● for status of the inputs	Yes
● for status of the outputs	Yes
Potential separation	
Potential separation digital inputs	
● between the channels, in groups of	2
Potential separation digital outputs	
● between the channels	Relays
● between the channels, in groups of	2
● between the channels and backplane bus	1 500 V AC for 1 minute
Permissible potential difference	
between different circuits	750 V AC for 1 minute
Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
cULus	Yes
FM approval	Yes

Subject to change without notice
© Copyright Siemens

RCM (formerly C-TICK)	Yes
KC approval	Yes
Marine approval	Yes
Ecological footprint	
● environmental product declaration	Yes
Global warming potential	
— global warming potential, (total) [CO2 eq]	123 kg
— global warming potential, (during production) [CO2 eq]	12.1 kg
— global warming potential, (during operation) [CO2 eq]	111 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-0.434 kg
Ambient conditions	
Free fall	
● Fall height, max.	0.3 m; five times, in product package
Ambient temperature during operation	
● min.	-20 °C
● max.	60 °C
● horizontal installation, min.	-20 °C
● horizontal installation, max.	60 °C
● vertical installation, min.	-20 °C
● vertical installation, max.	50 °C
● permissible temperature change	5°C to 55°C, 3°C / minute
Ambient temperature during storage/transportation	
● min.	-40 °C
● max.	70 °C
Air pressure acc. to IEC 60068-2-13	
● Storage/transport, min.	660 hPa
● Storage/transport, max.	1 080 hPa
Relative humidity	
● Operation at 25 °C without condensation, max.	95 %
Connection method	
required front connector	Yes
Mechanics/material	
Enclosure material (front)	
● Plastic	Yes
Dimensions	
Width	45 mm
Height	100 mm
Depth	75 mm
Weights	
Weight, approx.	230 g
Classifications	

	Version	Classification
eClass	16	27-24-22-04
eClass	14	27-24-22-04
eClass	12	27-24-22-04
eClass	9.1	27-24-22-04
eClass	9	27-24-22-04
eClass	8	27-24-22-04
eClass	7.1	27-24-22-04
eClass	6	27-24-22-04
ETIM	10	EC001419
ETIM	9	EC001419
ETIM	8	EC001419
ETIM	7	EC001419

Subject to change without notice
© Copyright Siemens

IDEA	4	3566
UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval					EMV
CCC	cULus	EAC	CE EG-Konf.	UKCA	KC

EMV	Test Certificates	Maritime application			
RCM	Special Test Certificate	ABS	BUREAU VERITAS	DNV	Lloyd's Register LRS

Maritime application	other			Environment
PRS	Confirmation	Confirmation	产品合格 QC PASS	Environmental Confirmations

last modified: 4/6/2025

Subject to change without notice
© Copyright Siemens