



Figure similar

connection cable PN for KTPX00(F) Mobile (PROFINET) length: 5 m, scope of supply: 1 connection cable

| General information                               |                                        |
|---------------------------------------------------|----------------------------------------|
| Product type designation                          | Connecting cable                       |
| Standards, approvals, certificates                |                                        |
| CE mark                                           | Yes                                    |
| cULus                                             | Yes                                    |
| RCM (formerly C-TICK)                             | Yes                                    |
| KC approval                                       | Yes                                    |
| Suitable for safety functions                     | Yes                                    |
| Ambient conditions                                |                                        |
| Ambient temperature during operation              |                                        |
| • min.                                            | 0 °C                                   |
| • max.                                            | 55 °C                                  |
| Ambient temperature during storage/transportation |                                        |
| • min.                                            | -20 °C                                 |
| • max.                                            | 60 °C                                  |
| Cables                                            |                                        |
| Cable length                                      | 5 m                                    |
| Maximum tensile load                              | 300 N                                  |
| Color of cable sheath                             |                                        |
| • green                                           | Yes                                    |
| Scope of supply                                   |                                        |
| Delivery quantity in pieces                       | 1                                      |
| Other                                             |                                        |
| Merchandise                                       | Yes                                    |
| Manufacturer name                                 | On request                             |
| Note:                                             | halogen-free according to EN 50267-2-1 |
| Classifications                                   |                                        |

|        | Version | Classification |
|--------|---------|----------------|
| eClass | 16      | 27-33-02-92    |
| eClass | 14      | 27-33-02-92    |
| eClass | 12      | 27-33-02-92    |
| eClass | 9.1     | 27-33-02-92    |
| eClass | 9       | 27-33-02-92    |
| eClass | 8       | 27-24-92-03    |
| eClass | 7.1     | 27-24-92-03    |
| eClass | 6       | 27-24-92-03    |

|        |    |             |
|--------|----|-------------|
| ETIM   | 10 | EC002584    |
| ETIM   | 9  | EC002584    |
| ETIM   | 8  | EC002584    |
| ETIM   | 7  | EC002584    |
| IDEA   | 4  | 3552        |
| UNSPSC | 15 | 32-15-17-03 |

Approvals / Certificates

General Product Approval



[Miscellaneous](#)



[China RoHS](#)

Further information

Usable in the following products: Detailed information can be found in the cross-list, which is available for download in the following SIOS note: 40466415  
<https://support.industry.siemens.com/cs/document/40466415/status-of-the-simatic-hmi-accessories-and-cross-list-update?dti=0&lc=en-WW>

last modified: 9/10/2025