



Figure similar

INOX frame 10" type 1, Unified stainless steel, type 1 for Panel, thin client and IPC, scope of supply: 1 frame 2 parts screwed together

| General information                               |                                                                          |
|---------------------------------------------------|--------------------------------------------------------------------------|
| Product type designation                          | protective frame INOX                                                    |
| Display                                           |                                                                          |
| Suitable for screen diagonal                      | 10.1 in                                                                  |
| Installation type/mounting                        |                                                                          |
| Mounting                                          | for mounting in a built-in widescreen Panel                              |
| Mounting type                                     | screw fixing                                                             |
| Mounting position                                 | Any, dependent on target device                                          |
| Front mounting                                    | Yes                                                                      |
| Mounting in portrait format possible              | Yes                                                                      |
| Mounting in landscape format possible             | Yes                                                                      |
| Degree and class of protection                    |                                                                          |
| IP (at the front)                                 | IP69                                                                     |
| Splashproof                                       | Yes                                                                      |
| Standards, approvals, certificates                |                                                                          |
| responsibility with the manufacturer              | Yes                                                                      |
| CE mark                                           | No; No CE marking obligation                                             |
| UL approval                                       | No                                                                       |
| REACH                                             | Yes                                                                      |
| RoHS conformity                                   | Yes                                                                      |
| FDA-compliant                                     | gaskets are FDA-compliant                                                |
| Ambient conditions                                |                                                                          |
| Suited for indoor use                             | Yes                                                                      |
| Suited for outdoor use                            | Yes; Always comply with the operating instructions of the target device. |
| Ambient temperature during operation              |                                                                          |
| • min.                                            | -40 °C                                                                   |
| • max.                                            | 80 °C                                                                    |
| Ambient temperature during storage/transportation |                                                                          |
| • min.                                            | -40 °C                                                                   |
| • max.                                            | 80 °C                                                                    |
| Relative humidity                                 |                                                                          |
| • Operation, max.                                 | 95 %                                                                     |
| Mechanics/material                                |                                                                          |
| Material                                          | Matte                                                                    |
| • Stainless steel                                 | Yes; V2A 1.4300                                                          |
| Enclosure material (rear)                         | Stainless steel V2A                                                      |
| Enclosure color (front)                           | matte, ceramic-blasted                                                   |
| Screw type                                        |                                                                          |

|                             |                                                                                                                     |
|-----------------------------|---------------------------------------------------------------------------------------------------------------------|
| • Torx                      | Yes; T20                                                                                                            |
| <b>Torques/forces</b>       |                                                                                                                     |
| • Tightening torque, min.   | 12 N·m; If there is not enough torque, the degree of protection on the front may not be guaranteed                  |
| • Tightening torque, max.   | 14 N·m                                                                                                              |
| <b>Dimensions</b>           |                                                                                                                     |
| Width                       | 307.2 mm                                                                                                            |
| Height                      | 232.2 mm                                                                                                            |
| Depth                       | 16 mm                                                                                                               |
| <b>Scope of supply</b>      |                                                                                                                     |
| Delivery quantity in pieces | 1; 1x protective frame INOX                                                                                         |
| • Parts per unit            | 1; 1x protective frame INOX incl. screws and seals (mounting frame and protective films can be ordered separately)  |
| <b>Other</b>                |                                                                                                                     |
| Merchandise                 | Yes; INOX frame                                                                                                     |
| Manufacturer name           | QUERUM products UG                                                                                                  |
| Manufacturer's address      | Wirtsstr. 23, 85110 Kipfenberg-Böhming, Germany                                                                     |
| contacting the manufacturer | email: querumproducts@web.de                                                                                        |
| Target devices              | Unified Comfort Panels, Industrial Thin Clients, Industrial Flat Panels and Industrial Pcs with suitable dimensions |
| Note:                       | Not released for hazardous areas and marine applications!                                                           |
| <b>Classifications</b>      |                                                                                                                     |

|        | Version | Classification |
|--------|---------|----------------|
| eClass | 16      | 27-33-02-92    |
| eClass | 14      | 27-33-02-92    |
| eClass | 12      | 27-33-02-92    |
| eClass | 9.1     | 27-33-02-92    |
| eClass | 9       | 27-33-02-92    |
| eClass | 8       | 27-24-92-03    |
| eClass | 7.1     | 27-24-92-03    |
| eClass | 6       | 27-24-92-03    |
| ETIM   | 10      | EC002584       |
| ETIM   | 9       | EC002584       |
| ETIM   | 8       | EC002584       |
| ETIM   | 7       | EC002584       |

|                                 |  |
|---------------------------------|--|
| <b>Approvals / Certificates</b> |  |
| other                           |  |

[Miscellaneous](#)

[Miscellaneous](#)

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Further information</b>                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Usable in the following products: Detailed information can be found in the cross-list, which is available for download in the following SIOS note: 40466415<br><a href="https://support.industry.siemens.com/cs/document/40466415/status-of-the-simatic-hmi-accessories-and-cross-list-update?dti=0&amp;lc=en-WW">https://support.industry.siemens.com/cs/document/40466415/status-of-the-simatic-hmi-accessories-and-cross-list-update?dti=0&amp;lc=en-WW</a> |

last modified:

4/22/2026 