



protective film 22"; front, type 6, for Industrial Flat Panel Basic, scope of supply: 10 protective films

| General information                               |                                                                                                                           |
|---------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| Product type designation                          | Protective film 22" type 6                                                                                                |
| Installation type/mounting                        |                                                                                                                           |
| Mounting in portrait format possible              | Yes                                                                                                                       |
| Mounting in landscape format possible             | Yes                                                                                                                       |
| Standards, approvals, certificates                |                                                                                                                           |
| CE mark                                           | No; No CE marking obligation                                                                                              |
| Ambient conditions                                |                                                                                                                           |
| Suited for indoor use                             | Yes                                                                                                                       |
| Suited for outdoor use                            | Yes; only suitable under certain conditions due to different environmental conditions; replacement cycle can be increased |
| Ambient temperature during operation              |                                                                                                                           |
| • min.                                            | -40 °C                                                                                                                    |
| • max.                                            | 80 °C                                                                                                                     |
| Ambient temperature during storage/transportation |                                                                                                                           |
| • min.                                            | -40 °C                                                                                                                    |
| • max.                                            | 80 °C                                                                                                                     |
| Relative humidity                                 |                                                                                                                           |
| • Operation, max.                                 | 90 %                                                                                                                      |
| • Condensation permissible                        | No                                                                                                                        |
| Mechanics/material                                |                                                                                                                           |
| Material                                          |                                                                                                                           |
| • plastic                                         | Yes; Autoflex EB Antiglare                                                                                                |
| Enclosure material (front)                        |                                                                                                                           |
| • plastic                                         | Yes; resistant to alcohols, diluted acids, diluted alkali, esters, hydrocarbons, ketones and household cleaners           |
| Dimensions                                        |                                                                                                                           |
| Width                                             | 531 mm                                                                                                                    |
| Height                                            | 326 mm                                                                                                                    |
| Thickness                                         | 0.2 mm                                                                                                                    |
| Scope of supply                                   |                                                                                                                           |
| Delivery quantity in pieces                       | 10; Units per set                                                                                                         |
| Other                                             |                                                                                                                           |
| printable with laser printer                      | No                                                                                                                        |
| Merchandise                                       | Yes                                                                                                                       |
| Manufacturer name                                 | Kolb-Siebdruck GmbH & Co. KG                                                                                              |
| Manufacturer's address                            | Espenstraße 5, 95632 Wunsiedel, Germany                                                                                   |
| Note:                                             | edge-adhesive, cannot be trimmed, for resistive touch systems or membrane fronts                                          |

| Classifications |        |         |                |
|-----------------|--------|---------|----------------|
|                 |        | Version | Classification |
|                 | eClass | 16      | 27-33-02-92    |
|                 | eClass | 14      | 27-33-02-92    |
|                 | eClass | 12      | 27-33-02-92    |
|                 | eClass | 9.1     | 27-33-02-92    |
|                 | eClass | 9       | 27-33-02-92    |
|                 | eClass | 8       | 27-24-92-03    |
|                 | eClass | 7.1     | 27-24-92-03    |
|                 | eClass | 6       | 27-24-92-03    |
|                 | ETIM   | 10      | EC002584       |
|                 | ETIM   | 9       | EC002584       |
|                 | ETIM   | 8       | EC002584       |
|                 | ETIM   | 7       | EC002584       |
|                 | IDEA   | 4       | 3552           |
|                 | UNSPSC | 15      | 32-15-17-03    |

Further information

Usable in the following products: Detailed information can be found in the cross-list, which is available for download in the following SIOS note: 40466415  
<https://support.industry.siemens.com/cs/document/40466415/status-of-the-simatic-hmi-accessories-and-cross-list-update?dti=0&lc=en-WW>

last modified: 8/2/2023 