



SIMATIC DP, connection module for power module PM-E ET 200 Pro ECOFAST
CU DP, 1x ECOFAST connection RS-485; product phase-out planned – see SIOS
109989704

Input current	
from load voltage 2L+ (without load), max.	10 A
Accessories	
Function description	Feeding of load voltage 2L+ within a station; 1x ECOFAST Cu
belongs to product	ET 200pro; PM-E DC24V
Dimensions	
Width	45 mm
Height	130 mm
Depth	60 mm
Weights	
Weight, approx.	125 g
Classifications	

	Version	Classification
eClass	16	27-24-26-03
eClass	14	27-24-26-03
eClass	12	27-24-26-03
eClass	9.1	27-24-26-03
eClass	9	27-24-26-03
eClass	8	27-24-26-03
eClass	7.1	27-24-26-03
eClass	6	27-24-26-03
ETIM	10	EC001598
ETIM	9	EC001598
ETIM	8	EC001598
ETIM	7	EC001598
IDEA	4	3560
UNSPSC	15	32-15-17-04

Approvals / Certificates	
General Product Approval	



[Miscellaneous](#)[Manufacturer Declaration](#)



General Product Approval	Maritime application
--------------------------	----------------------



[China RoHS](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

Maritime application

[KR \(Korean Register of Shipping\)](#)

last modified:

4/7/2025