



nakładka łączeniowa szyna rozdzielcza pola do góry i w dół 30 x 10 mm, system: stopniowany, główna szyna zbiorcza: z tyłu, głęb.: 800 mm



Wersja	
Nazwa markowa produktu	SIVACON S4
Ogólne dane techniczne	
liczba biegunów	4
komponenty połączenia elektrycznego	Pole/pole
Obwód główny	
prąd roboczy wartość znamionowa	1 190 A
moment dokręcenia maksymalny	40 N·m
Konstrukcja mechaniczna	
wysokość	50 mm
szerokość	85 mm
głębokość	200 mm
Waga netto na jedn.	12,15 kg
Zezwolenia Certyfikaty	
Environment	General Product Approval

[Environmental Con-
firmations](#)

[Environmental Con-
firmations](#)



[Confirmation](#)

General Product Approval

other

[Miscellaneous](#)



[Confirmation](#)



Więcej informacji

Informacje dotyczące opakowania

[Informacje dotyczące opakowania](#)

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8PQ4000-5BA67>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/pl/ps/8PQ4000-5BA67>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8PQ4000-5BA67

CAX-Online-Generator

<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>

Krzywe charakterystyczne

[https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP="HAUPT"></mmp_prod_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP=)

Ostatnia zmiana:

11.06.2025 

