



nakładka łączeniowa szyna rozdzielcza pola do 8 x 30 x 10 mm system: niestopniowany, główna szyna zbiorcza: dupleks, pozycja: z lewej u góry, z prawej na dole, głęb.: 800 mm szer.: 200 mm

Wersja	
Nazwa markowa produktu	SIVACON S4
Ogólne dane techniczne	
liczba biegunów	4
komponenty połączenia elektrycznego	Pole/pole
Obwód główny	
prąd roboczy wartość znamionowa	3 700 A
moment dokręcenia maksymalny	40 N·m
Konstrukcja mechaniczna	
wysokość	50 mm
szerokość	85 mm
głębokość	200 mm
Waga netto na jedn.	18,5 kg

Zezwolenia Certyfikaty	
Environment	General Product Approval

[Environmental Con-  
firmations](#)



[Environmental Con-  
firmations](#)



[Confirmation](#)

General Product Approval

other



[Miscellaneous](#)



[Confirmation](#)



### Więcej informacji

Informacje dotyczące opakowania

[Informacje dotyczące opakowania](#)

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8PQ4000-5BA88>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/pl/ps/8PQ4000-5BA88>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[https://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=8PQ4000-5BA88](https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8PQ4000-5BA88)

CAX-Online-Generator

<https://www.siemens.com/cax>

**Tender specifications**

<https://www.siemens.com/specifications>

**Krzywe charakterystyczne**

[https://curves.simaris.siemens.com/curves/<mmp\\_prod\\_noCOMP='HAUPT'></mmp\\_prod\\_no>](https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP='HAUPT'></mmp_prod_no>)

---

Ostatnia zmiana:

3.03.2026 

