

profil wkładany, do 50mm² zacisków, wyrównuje pryzmatyczne dno tulei przy zastosowaniu przewodów taśmowych



Wersja		
Nazwa markowa produktu	SETRON	
oznaczenie produktu	Profil wkładany	
wykonanie produktu	Mostek	
Wygląd		
kolor	Pozostałe	
wyposażenie produktu ochrona przed dotykiem	Nie	
właściwość produktu elektrycznie izolowany	Tak	
akcesoria	Inne	
Konstrukcja mechaniczna		
rodzaj montażu	Inne	
wielkość styku	20 mm	
Waga netto na jedn.	5 g	
Zezwolenia Certyfikaty		
Environment	General Product Approval	other

[Environmental Confirmations](#)



[Confirmation](#)



EG-Konf.

[Confirmation](#)



Więcej informacji

Informacje dotyczące opakowania

[Informacje dotyczące opakowania](#)

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WH9020-3MA00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/pl/ps/8WH9020-3MA00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH9020-3MA00

CAX-Online-Generator

<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>

Krzywe charakterystyczne

https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP='HAUPT'></mmp_prod_no>

