



system szyn zbiorczych, akcesoria odległość środków szyn 60 mm uchwyt szyn zbiorczych N/PE do szyn 12x 5 (10)-30x 5 -10 i 6x 6mm, instalacja wolnostojąca lub montaż do 8US1923-2AA01

Wersja	
Nazwa markowa produktu	SETRON
oznaczenie produktu	Belka szyny zbiorczej
wykonanie produktu	N/PE
napięcie robocze przy AC wartość znamionowa	690 V
możliwość zastosowania	Szyny płaskie
rodzaj przekrojów poprzecznych możliwych do podłączenia przewodów dla przewodów Cu wielożyłowy	12 mm x 5 mm – 30 mm x 10 mm
Konstrukcja mechaniczna	
odstęp między środkami szyn	60 mm
Waga netto na jedn.	52 g
Zezwolenia Certyfikaty	
Environment	General Product Approval

[Environmental Conformations](#)

[Environmental Conformations](#)



[Confirmation](#)

General Product Approval	Test Certificates	other
		Miscellaneous
		Miscellaneous
		Confirmation

Więcej informacji

Informacje dotyczące opakowania

[Informacje dotyczące opakowania](#)

Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8US1923-1AA01>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/pl/ps/8US1923-1AA01>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

https://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8US1923-1AA01

CAX-Online-Generator

<https://www.siemens.com/cax>

Tender specifications

<https://www.siemens.com/specifications>

Krzywe charakterystyczne

https://curves.simaris.siemens.com/curves/<mmp_prod_noCOMP='HAUPT'></mmp_prod_no>

Ostatnia zmiana:

1.06.2026 

